

Administration & Configuration Guide

August 2026

How it Works: The Building Blocks

Primero is an information management system that allows for data entry and reporting for child protection (CPIMS+) and gender-based violence (GBVIMS+). The system helps intake relevant information via multiple sources, consolidates the information into relevant record types (Cases / Incidents) and allows service providers to report and make educated decisions to assist in these locations.

Records

Primero uses three types of "records" to represent protection-related information:

- **Case (for CPIMS+ and GBVIMS+)** - This represents an individual beneficiary.
- **Incident (for CPIMS+ and GBVIMS+)** - This represents an event that has occurred. This is often an incident of violence or an encounter with the beneficiary outside of the typical case management process.
- **Tracing Request (for CPIMS+)** - This represents an individual seeking to be reunified with one or more unaccompanied or separated children. Tracing Requests are used primarily in Family Tracing and Reunification programming.

Each of these three "record types" will contain a different set of information, depending on the system's configuration, and which Primero Modules are in use.

Users

Primero **Users** are the individuals working for service-providing organizations and agencies who use the system.

User Groups

User Groups represent teams of users working together.

For example in CPIMS+, there may be a team of social workers in a particular district providing services to children. There may be another team responsible for the child's best interest determination. A manager of a user group will have some level of access to all of the data managed by that group, but not to the data managed by a different group.

For example in GBVIMS+, there may be a team of GBV Case Workers in a particular district providing services to survivors of GBV. There may be a GBV case management supervisor who needs to review safety plans to ensure effective case management. The case management supervisor of a user group will have some level of access to all of the data managed by that group, but not to the data managed by a different group.

Roles

Users will have a **Role**, which defines what particular users are allowed to do: for instance viewing records, editing records, creating reports, or configuring the system. Examples of roles in CPIMS+ are Social Worker, CP Manager, and CP Administrator.

Along with defining what actions the user is allowed to perform, roles also limit what kind of information is visible about individual records for a specific user. For example, a CP Social Worker may be allowed to view and edit personally identifiable information (such as name, age, and sex) about a particular client, while a CP Manager may only see a reduced set of information about that same person (age and sex, but not the name), and may not be allowed to edit any of it.

Examples of roles are GBV Case Worker, GBV Case Management Supervisor, and GBV Organization Focal Point.

Along with defining what actions the user is allowed to perform, roles also limit what kind of information is visible about individual records for a specific user. For example, a GBV Case Worker may be allowed to view and edit personally identifiable information (such as name, age, and sex) about a particular survivor, while a Case Management Supervisor may see the case and incident record for that same person, but may not be allowed to edit any of it.

The general term for these limits to what the user can do and what a user can see is *authorization*.

Fields

A **field** (data field) is information within a record. Fields are attributes like name, age, date of birth. Sometimes one field can be used to store several values like a list of protection concerns or all the languages spoken. Fields types include:

- Text Field
- Text Area
- Date
- Date-Time
- Date Range
- Tick Box
- Select Drop Down
- Multi-Select
- Radio Button
- Numeric Field
- Tally Field

Each of these field types is defined in the [Form and Field Configuration](#) section of this guide.

Forms

A **Form** contains a set of fields for a record. By configuring the Primero application, you can specify new fields on a form, reorder the fields, or allow different forms to share the same field. In general, fields are organized into forms which represent steps in the user's workflow. For instance, an administrator may add the "Risk Level," and "Protection Concerns" fields to a "Preliminary Assessment" form on the Case record, since case workers collect both these pieces of information during the Preliminary Assessment step of the case management process.

Form Groups

Form Groups appear in the form navigation menu on the left side of the screen when a user is creating, viewing, or editing a record. When a user clicks a form group, it expands or collapses to either show or hide the forms it contains.

For example in CPIMS+, the "Registration" form group might contain the forms "Child's Details," "Care Arrangements," and "Interview Details." Form Groups keep the form navigation menu organized.

For example in GBVIMS+, the "Record Information" form group when creating, viewing or editing cases, might contain the forms "Record Information," "Approvals," and "Incidents." Form Groups keep the form navigation menu organized.

Getting Started

Where to Make Configuration Changes

It is recommended that configuration design take place on a separate sandbox or "demo" instance. This will buffer live end users from experiencing potential errors from misconfigured forms and roles. Once the configuration has been successfully modified, it can then be applied to production as an import of the Configuration. For more information on how to send configuration from a sandbox or "demo" site to a production site, please see the [Managing Configurations](#) section of this guide.

Sequencing Configuration Work

Some elements of Primero configuration depend on others. For this reason, we recommend configuring your system in the following order:

- **Forms and Lookups:** Decide which forms contain which information. Creating Forms is necessary to specify each Role's Form access. In addition, you must specify options for the "Service Type" lookup before you can set the Service configuration for Agencies and Users.

- **Agencies, User Groups, Roles:** All of these must be configured before you can create Users.
- **Users:** While you can create User accounts to test your configuration, you should avoid creating production users until implementation partners have fully reviewed and approved the rest of the configuration.
- **Reports:** You can begin configuring Reports any time after configuring your Forms, but administrators will continue creating and updating Reports after go-live.

Note: You can configure the **Contact Information** at any point.

Navigating Settings

To begin configuring Primero, click on the **Settings** link in the navigation menu.

The screenshot displays the GBVIMS+ application interface. On the left is a vertical navigation menu with the following items: Home, Cases (with a yellow badge showing '58'), Incidents, Tracing Request, Reports, Exports, Support, primero (user profile), Settings (highlighted with a gear icon), and Log out. The main content area is divided into two panels: 'SETTINGS' and 'USERS'. The 'SETTINGS' panel has a list of options: Users (highlighted), Roles, User Groups, Agencies, Forms (with a dropdown arrow), Locations, Contact Information, Configurations, and Audit Logs. The 'USERS' panel shows a table with the header 'FULL NAME' and five rows of user names: ASANTE AKIM CENTRAL MUNIC, ASANTE AKIM CENTRAL MUNIC, ASANTE AKIM CENTRAL MUNIC, ADANSI ASOKWA DISTRICT ASS, and ADANSI ASOKWA DISTRICT ASS.

Note that both “Forms” and “Lookups” can be found in the “Forms” section of the Settings navigation menu.

Form and Field Configuration

Forms determine how information is organized in Primero and help control which users can see which types of information about a record.

A **Form** contains a set of fields for a record. As an administrator in Primero, you can create a new form, modify the existing forms, specify new fields on a form, reorder the fields, or allow different forms to share the same field.

A **Field** (data field) is information within a record. Fields are attributes like name, age, date of birth. Sometimes one field can be used to store several values like a list of protection concerns or all the languages spoken. The same field can be 'shared' on different forms so that you can enter a date of birth on one form and see it on multiple forms.

The Forms List

To configure Forms, first click on the "Forms" section within the Settings navigation menu, then click the "Forms" link that appears.

The screenshot displays the 'FORMS' section in the Primero application. The left sidebar contains the navigation menu, with 'Settings' selected. The main content area is titled 'FORMS' and shows a list of forms organized by group. The 'Assessment' group is expanded, showing a table of forms. On the right, there are filters for 'Record Type' (Case, Tracing Request, Incident) and 'Module' (CP).


Form Name	Record Type	Module
Assessment Status	Case	CP
Protection Concerns	Case	CP
Assessment	Case	CP
Care Assessment	Case	CP
Best Interest	Case	CP
Protection Concern Details	Case	CP
Child Under 5	Case	CP
CAAFAG Profile	Case	CP

Here, you will see Forms organized by Form Group. Click on a Form Group to expand it and see the forms contained within.

Note that this list only shows Forms for a given Module and Record Type at a given time (e.g. CP Cases or GBV Cases). You can use the filters on the right side of the page to change which Forms you are viewing.

Reordering Forms

To update the order in which Forms appear, click the “Reorder” button at the top of the list. Then drag and drop Forms and Form Groups into the desired order. Click the “Save Changes” button once you are finished.




The screenshot shows a sidebar on the left with a list of categories: 'ers', 'les', 'er Groups', and 'encies'. A red box highlights a 'REORDER' button with a list icon. Below this, a table lists forms and form groups. The table has three columns: a list icon, a name, a type, and a category. The items are: 'Data Confidentiality' (Form Group), 'Identification / Registration' (Form Group), 'Best Interest' (Case), 'Child Under 5' (Case), 'Protection Concern Details' (Case), 'CAAFAG Profile' (Case), 'Summary and Conclusions' (Case), 'BID Status' (Case), 'BID Report' (Case), and 'Family / Partner Details' (Form Group). At the bottom right, there are 'CANCEL' and 'SAVE CHANGES' buttons.

	Data Confidentiality		
	Identification / Registration		
	Best Interest	Case	CP
	Child Under 5	Case	CP
	Protection Concern Details	Case	CP
	CAAFAG Profile	Case	CP
	Summary and Conclusions	Case	CP
	BID Status	Case	CP
	BID Report	Case	CP
	Family / Partner Details		

Creating a Form

To create a new form, click the “New” button at the top of the Forms List.



The screenshot shows the 'ADD FORM' interface. At the top, there is a 'FORMS' header with a '+ NEW' button. Below this, there is a 'SETTINGS' tab selected, with 'FIELDS' and 'TRANSLATIONS' tabs also visible. The 'Settings' section contains the following fields: 'Form Title *' (with a note 'Must be entered in English'), 'Form Description *' (with a note 'Summarize form purpose. Must be entered in English'), 'Form Group *' (with a note 'Place form into a related group for users'), 'Record Type *' (a dropdown menu), and 'Module *' (a dropdown menu). At the bottom right, there are 'CANCEL' and 'SAVE' buttons.

FORMS + NEW

SETTINGS **ADD FORM** X CANCEL ✓ SAVE

Users

Roles

User Groups

Agencies

Forms ^

Forms

Lookups

Locations

Contact Information

Configurations

Audit Logs

SETTINGS FIELDS TRANSLATIONS

Settings

Form Title *

Must be entered in English

Form Description *

Summarize form purpose. Must be entered in English

Form Group *

Place form into a related group for users

Record Type *

Module *

Fill in the following information about the form:

- **Form Title** - This is the name of the Form that will appear in the List of Forms in the Left Navigation panel.
- **Form Description** - This is a description of the form. Later, when you are configuring which Forms a Role can access in the Role form, hovering your mouse over the Form name will reveal this Description, to remind you what information you included in this Form, and how it is used.

- **Form Group** - This is the name that displays in the Left Navigation Panel at the top level when forms are grouped. The Form Group has a dropdown carrot to the right of the name in the Left Navigation Panel. Clicking on this carrot expands or contracts the Form Group. To add the Form Group Name, you can select an existing Form Group from the dropdown list or add a new one. To add a new one, type the desired name in the box directly below the field and then click on the phrase 'Click to add <form group name>' directly below that:

If you create a new form group for your form, it will appear later in one of the Form Group lookups. You will be able to edit and provide a translation for your form group there. For more information on how to edit form groups, see the section [Managing Form Groups](#).

If you want the form to appear by itself and not as part of a Form Group, you must enter your Form's name in the Form Group Name field, then click the option to create a new Form Group with this name.

Be sure to specify whether your form is visible.

Visibility

Show on



Web App



Mobile App



Skip Logic?

Press the **Save** button when all the desired information is entered.

Adding and Updating Fields

You must create and save a Form before you are able to add fields to it. Once you have saved the Form, click the “Fields” tab.

FAMILY DETAILS

✕ CANCEL

✓ SAVE

SETTINGS

FIELDS

TRANSLATIONS

Here, you can add, update, or reorder any fields in this form.

Fields

+ ADD FIELD

NAME	TYPE	SHOW?
------	------	-------

To add a field to the form, select the ADD button. The following will appear:

ADD FIELD



 CREATE NEW FIELD

 ADD EXISTING FIELD

 CANCEL

You have two options:

- **Create New Field:** This will create a completely new field on the form. You will get to choose the type of field as well as its options.
- **Add Existing Field:** This will copy an existing field from a different form onto this form. When a user is updating a record, if they enter a value on this field in the first form, the same value will appear automatically on the copied field in the second form. If you choose this option, you will not be able to choose a field type, and you will not be able to update all of the field's configuration options.

Create New Field

If you select the "Create New Field" option, you will be prompted to select a field type. Please be careful selecting the field type: *once you have selected a field type and saved the field, you will not be able to change the field type.*

Text Field	
Text Area	
Tick Box	☒
Select Drop Down	
Radio Button	☒ ☐
Multi-select	
Numeric Field	
Date Field	
Date-Time	 
Separator	Separator
Subform	

A brief description of each field type and any additional information to build the field is detailed below:

- **Text Field** - A Text Field is used for brief pieces of text. Unlike a Text Area, it will not expand to fit the text entered. Text will not be truncated but it is not easy to view.
- **Text Area** - Unlike a Text Field, a Text Area will expand to fit the text entered.
- **Tick Box** - A tick box is a checkbox with one selection as shown below:



- **Select Drop Down** - A select drop down field allows the user to pick a value or values from a defined list of options as shown below:

What are the client's current care arrangements?

(Select...)

Biological parents and family

Extended family

Foster parents

Adopted parents

Institutional care

Independent living

Other (please specify in your notes)

- **Radio Button** - This is similar to a Select Drop Down, since users can only select one option at a time. Note that, once a user selects an option, they cannot go back to having no options selected. This field type is typically used for Yes / No questions.
- **Multi-Select** - This is similar to a Select Drop Down, except that a user may select as many options as they like.
- **Date Field** - The date field type will automatically validate that what the user enters is a valid date field. The standard date format for Primero is dd-mmm-yyyy.
- **Date-Time** - This is similar to a Date Field, except that users can specify a time of day, in addition to a date.
- **Separator** - This is a header which separates one section of a form from another. For instance in CPIMS+, if the Child's Details form contains a number of fields about contact information for a child (e.g. "Location," "Address," "Phone Number"), you may add a Separator above these fields with the label, "Contact Information for the Child."

See example below from GBVIMS+: the Survivor Assessment form contains a number of fields about a survivor (e.g. "Survivor's family situation," "Survivor's current living situation," "Survivor's occupation or role"). There is a Separator above these fields with the label, "Survivor Profile" to distinguish these points from the "Key Assessment Points" below."

SURVIVOR ASSESSMENT

Survivor Profile

Guidance

Survivor's family situation (for adults)

Guidance

Survivor's current living situation

Guidance

Survivor's occupation or role

Guidance

Specific considerations for child survivors

Guidance

Reasons for seeking case management services

Guidance

Describe what happened to the survivor in the survivor's own words

Guidance

Key Assessment Points

Guidance

Current situation and imminent risks

Guidance

- Subform** - The Subform is a section of a form where a user can collect the same set of data for multiple occurrences within the same Case, Incident or Tracing Request. For example, to collect information on a Case's family members, a user may enter the "Name," "Relationship to the Case," "Age," and "Sex" for multiple people. For this reason, these fields appear in the "Family Details" Subform, where the user adds an entry for each family member. See example below for CPIMS+:


Add Intervention plans and services details

+ ADD

!

No Intervention plans and services details found. They need to be added.

In GBVIMS+, a case worker can complete the Psychosocial Functionality Scale with a survivor multiple times throughout the case management process. For this reason, this questionnaire appears in the "PSS" Subform, where the user adds an entry for each survey completed by the survivor. See example below:




PSYCHOSOCIAL FUNCTIONALITY SCALE

Add PSS Subform

 No PSS Subform found. They need to be added.

+ ADD

Once a type of field is selected, the fields required to create that type of field will appear.



ADD MULTI-SELECT ×

Name *

Must be entered in English

Help Text

Must be entered in English

Guidance

Must be entered in English

☐ Required

☒ Enabled

Below are the attributes you will need to specify for a field, though you will only need to specify some of these, depending on which field type you selected.

General Field Attributes

- **Display Name** - This is the field label that will display on the form
- **Help Text** - The help text will appear below the field and only in Edit mode. The help text is not visible when you are only viewing the record. This allows you to provide some guiding language to give the user a frame of reference for the proper answer or how to come to a conclusion based on information provided.
- **Guidance** - Similar to Help Text, Guidance is text you display to users to give guidance on how to fill out the field. Generally, Guidance is for guiding text which is too long to put into Help Text. Users view Guidance by clicking the "Guidance" link below a field, at which point a small box appears containing the configured Guidance text.

- **Required** - If a field has this attribute checked, users will not be able to save a record without filling out the field. Note that if a field inside a subform is required, users will only be required to fill out the field if they have already added an entry into that subform.
- **Enabled** - Set to checked by default, this attribute determines whether users can update information in a field, or whether they can only view that information. If this is checked, users can update information in the field; if not checked, they cannot update the field's information.

Specifying Field Options

For Select Drop Downs, Multi-Selects, and Radio Buttons, there are two ways to specify options:

- **Use Pre-Defined Lookup** - A Lookup a list of options that can be reused across multiple fields. For example, the Country Lookup (containing the names of all the world's countries) is used by fields like "Nationality" and "Country of Origin." Using a lookup helps you avoid specifying the same options multiple times when configuring forms. *It is highly recommended to use Lookups whenever possible.* For more information on Lookups, as well as how to create and update them, see the [Lookup Values Management](#) section of this guide.
- **Create Unique Values** - If your field will need options that will not be used by any other fields, you can specify unique option values.

To specify a Lookup to use for your field's options, click the "Use Pre-Defined Lookup" tab in the "Options" section of the form. Then begin typing in the "Find Lookup" field to search for the Lookup you want.

OPTIONS

You may use either pre-defined lookups or create unique values.
You cannot do both.

USE PRE-DEFINED LOOKUP CREATE UNIQUE VALUES

Find Lookup

prot

- Protection Concerns
- Protection Status

Once you have selected a Lookup, you can also choose one of the Lookup's options to be selected by default when a user creates a new record.

To specify unique options, click the “Create Unique Values” tab. Add as many options as you want. Use the radio buttons in the “Default” column to select which option should be populated by default when a user creates a new record. You can drag-and-drop options to rearrange them.

NOTE: Please be careful when selecting options. Once you have saved a field, you will not be able to ...

- Change the Lookup used for its options
- Switch from using a Lookup to using unique option values.
- Delete options from Unique Values.

Setting Visibility

At the bottom of the Add Field pop-up, you will see four tick boxes which control where the field appears.

VISIBILITY

Show on

☒ Web app	☒ Mobile app	☒ Show page	☐ Short form	☐ Skip Logic?
---	--	---	-------------------------------------	--------------------------------------


- **Web app** - This controls whether the field appears for users when they are viewing, editing, or creating a record.
- **Mobile app** - NOTE: This attribute no longer controls anything. It may be removed in the future.
- **Show page** - Checking this box allows the user to see the field when they are viewing a record. If the box is unchecked, the field will only be visible when they are creating or editing a record.
- **Short form** - If this box is checked, the field will appear to users who are previewing records they cannot access. Note that this attribute will not appear for fields which are located within subforms. **Note:** if you would like to “hide” the photo from appearing in the preview modal when a case worker searches for a case, preview modal, then edit the "Photos and Audio" form, click into the "Photos" field and, under "Visibility," uncheck "Short form".
- **Skip logic?** - Checking this box allows the user to add conditions on the field to enable skip logic. Go to “Specialized Attributes” to read more about skip logic.

Specialized Attributes

Some form attributes only appear for specific types of fields:

- **Skip Logic** - Conditions can be made on specific forms and fields where you can “skip” specific forms or fields based on a response on another question. In order to enable skip logic, you will select the “Skip Logic?” tick box under “Visibility” on the form itself or within a field in a specific form. Once ticked, you will be able select the “Add Condition” which will allow you to select a specific response which would ensure a question or form is skipped. You can set multiple visibility conditions for a form and combine them, saying either that all conditions need to be true or only one needs to be true. [Here is a short](#)

[video](#) providing guidance on how to configure skip logic.



The screenshot shows a modal window titled "ADD CONDITION" with a close button (X) in the top right corner. Inside the modal, there are three input fields: "Field Name", "Condition", and "Value". Each field has a dropdown arrow on its right side. At the bottom of the modal, there are two buttons: a blue "Add" button with a checkmark icon and a grey "Cancel" button with an X icon.

Note: Let's say you create a skip logic where B will only show if you select A, and C will only show if you select B. If you add a value for A, and then later hide A, it does not hide C. This is by design, since clearing out the values for fields once they were hidden could cause confusion with users.

- **Tick Box**

- **Tick Box Label** - This is the label which appears to the right of a tick box. If left blank, users will see the word "Yes" to the right of the box, as seen below.

Consent has been given for the child to participate in the case management process

☐ Yes

If consent has not been provided, do not select

-
- **Date Field and Date-Time**

- **Cannot be in future** - Checking this box will prevent users from entering dates or times in the future for this field.
- **Defaults to current date?** - If this box is checked, users creating a new record will see this field with the current date automatically filled. For **Date-Time** fields, this attribute appears as "**Defaults to current date and time**," since users creating new records will see the field automatically filled out with the current date and time.

Adding a Subform

If you select "Subform" as the field type, you will see specialized attributes for Subforms.

- **Subform Title** - This will appear at the top of the modal for adding subforms, and as part of the header above your subform. See example below.

- **Subform Description** - This description is only visible to administrators.
- **Selective Syncing on Mobile** - NOTE: This attribute no longer controls any functionality. It may be removed in the future.
- **Prevent subform entry removal?** - Checking this box will prevent users from removing a subform entry once they have added it. This is typically used for subforms which are critical to Primero functionality, such as the Services subform.
- **Start with one subform entry?** - If this box is checked, when users create a new record, they will see one blank entry automatically added for this subform. Note that selecting this setting while including required fields in your subform can help ensure users fill out at least one subform entry on record creation.
- **Tally Field**
 - **Tally Items** - These are the items which users will tally (up to a maximum of 5 items) as seen below.

TALLY ITEMS (5 MAXIMUM)

	ENGLISH TEXT	REMOVE
⋮	Boys	
⋮	Girls	



Once Boys and Girls are added, the tally looks like this on the form:

Number of Boys and Girls in Direct Family		
Boys	Girls	Total
2	3	5

Add Existing Field

To copy a field to your form which has already been created on another form, click the “Add Existing Field” button after clicking the Add field button.

ADD FIELD



 CREATE NEW FIELD

 ADD EXISTING FIELD

 CANCEL

In the search box, type to find a field. Click the ‘+’ next to the field you want to add.

ADD FIELD

CREATE NEW FIELD

×

Q

Risk

NAME	TYPE	FORM	
Risk Level	Select Drop Down	Assessment	—
Summary of reasons for risk level	Text Area	Assessment	+
Risk Level	Select Drop Down	Protection Concerns	+
Risk Level	Select Drop Down	Summary and Conclusions	+
Summary of reasons for risk level	Text Area	Summary and Conclusions	+

Rows per page: 10 ▾

1-5 of 5

<

>

✓ SELECT

×

CANCEL

Once you have selected the field, search for other fields to add. If you want to deselect a field, click the ‘-’ which appears where the ‘+’ was previously. Click the “Select” button when you are done.

Updating Fields

To edit a field, go to the Fields tab of the form editor, then click the field you want to edit. Editing a field is very similar to adding a field, with the following exceptions:

- You cannot change a field from one type to another. If you would like to change a field’s type, you must create a new field with the desired type, then hide the field you are replacing.
- You will not be able to change all of your field’s option configuration. Specifically, you will not be able to ...
 - Change the Lookup used for its options
 - Switch from using a Lookup to using unique option values.
 - Delete options from Unique Values. Instead, if you no longer want one of your unique values to appear, you can deselect the tick box next to the option in the “**Enabled**” column of the option list. This will prevent users from selecting this option in the future.

ENGLISH TEXT	DEFAULT?	ENABLED?
Child	☐	☒
Caregiver	☐	☒
Other	☐	☒

+ ADD ANOTHER OPTION X CLEAR DEFAULT

Note: You cannot delete fields in Primero. If you created a field by mistake or do not want it to appear in the forms anymore, you can hide it using the **“Visibility”** tick boxes in the Edit Field modal.

Editing an Existing Form

To edit an existing form, go to the Forms list and click the form you would like to edit. You will automatically arrive at the Edit Form page. Once you have made changes, **be sure to click the Save button**. If you do not click Save, your changes will be lost.

Editing a form is mostly similar to creating a form. Note that you cannot add fields or translations for your form until you have saved it.


Change the Field Order within a Form

While editing a form, you can change the order of fields. Drag and drop fields using the “grip” at the left side of the fields table.

SETTINGS FIELDS TRANSLATIONS		
Fields + ADD FIELD		
NAME	TYPE	SHOW?
Protection Status	Select Drop Down	☐
Urgent Protection Concern?	Radio Button	☐
Risk Level	Select Drop Down	☒
Population Group	Select Drop Down	☒
If Other, please specify	Text Field	☒
UNHCR Protection Code	Text Field	☐
Protection Concerns	Multi-select	☒
If Other, please specify	Text Field	☒


Change the Form Group

While creating or editing a form, you can change the form group by clicking into the Form Group field. Begin typing the name of the form group you want and then select one of the results that appears.



A screenshot of a web form's 'Form Group' field. The field is labeled 'Form Group *' and contains the text 'Case Plan'. A dropdown menu is open, showing a list of form groups: 'Action Plan', 'Alleged Perpetrator', 'Assessment', 'BIA Form', 'CP Incident', 'CP Individual Details', 'Case Closure', and 'Case Conference Details'. The 'Action Plan' option is highlighted. A close button (X) is visible in the top right corner of the dropdown menu.

To add a new form group, type the name of the new form group in the field. Then click the “Add” option that appears. Once you save the Form, this new Form Group will be added.



A screenshot of a web form's 'Form Group' field. The field is labeled 'Form Group *' and contains the text 'Risk Factors'. Below the text input, there is a button labeled 'Add "Risk Factors"'. A close button (X) is visible in the top right corner of the field.

Providing Translations

NOTE: You cannot provide translations for a form until it has been saved. You must create and save a form with its English name before you can provide translations.

To provide translations for a Form's main attributes, click the **Manage Translations** button on the Settings tab.

SETTINGS FIELDS TRANSLATIONS

Settings

Form Title *

Protection Concerns

Must be entered in English

Form Description *

Contains preliminary assessment information, including risks to the child's welfare.

Summarize form purpose. Must be entered in English

Module *

CP

Record Type *

Case

Form Group *

Place form into a related group for users

MANAGE TRANSLATIONS

The Manage Translations modal will open. Select a language from the “Select language” dropdown, then enter your translations. Click the **Update** button when you are done.

EDIT TRANSLATIONS

×

Select language *

Français

FORM TITLE

English: Protection Concerns

DESCRIPTION

English: Contains preliminary assessment information, including risks to the child's welfare.

✓ UPDATE

✕ CANCEL

You can also provide translations by clicking on the **Translations** tab in the Form Editor. Here, you can provide translations for settings like the Form Title and Description, as well as for the display names of any fields. Be sure to select your translation language before entering translation text.

SETTINGS

FIELDS

TRANSLATIONS

Translations

Note: To add translations for the Form Group, you need to edit the Form Group lookup translations. [Edit Form Group lookup.](#)

Select language

Français

Forms

DETAIL	ENGLISH TEXT	TRANSLATION TEXT
Form Title	Protection Concerns	
Form Description	Contains preliminary assessment information,	

Fields

DETAIL	ENGLISH TEXT	TRANSLATION TEXT
Protection Status	Protection Status	MANAGE
Urgent Protection Concern?	Urgent Protection Concern?	MANAGE

If you would like to provide more detailed translations for a field, click the **Manage** button next to that field. The Manage Translations modal will appear for that field. Select the language, provide translations, and click **Update** when done.

EDIT TRANSLATIONS

×

Select language *

Français

DISPLAY NAME

English: Consent/Assent Obtained From

HELP TEXT

English:

GUIDANCE

English:

OPTIONS


ENGLISH TEXT	TRANSLATION TEXT
Child	
Caregiver	

✓ UPDATE

×

CANCEL

You can also provide translations for field attributes in the Edit Field modal. Go to the Fields tab of the Form Editor and click a Field to edit it. Then, inside the Edit Field modal, click the **Manage Translations** button.



The screenshot shows the 'EDIT FIELD' modal with a close button (X) in the top right corner. The modal contains several sections: 'Name *' with the value 'Protection Concerns', a note 'Must be entered in English', and 'Database Name: protection_concerns'; 'Help Text' with a note 'Must be entered in English'; 'Guidance' with a note 'Must be entered in English'; a 'Required' checkbox (unchecked) and an 'Enabled' checkbox (checked); and a 'MANAGE TRANSLATIONS' button highlighted with a red rectangular box. Below this is an 'OPTIONS' section with the text 'You may use either pre-defined lookups or create unique values. You cannot do both.' At the bottom are 'UPDATE' and 'CANCEL' buttons.

The same Manage Translations modal will appear for the field. Select a language, enter translation text, then click **Update** when you are done.

Once again, please be sure to click the **Save** button at the top of the Form Editor page once you are done making any changes to Form or Field translations.


Note: While you can manage unique field options in the Manage Translations modal, you cannot use this interface for translating Lookup options. For information on how to translate Lookup options, please see the **Lookup Values Management** section of this guide.

Note: if you are changing a translation for a field that is shared on multiple forms, please follow these steps:

1. Update the name translation in the original field
2. Remove the fields which shared the original field if there is no data to be preserved
3. Re-add the field to the other forms

Lookup Values Management


“Lookup” is the term used for a set of values that might be used as the dropdown options for multiple fields. For example, the Country Lookup (containing the names of all the world’s countries) is used by fields like “Nationality” and “Country of Origin.” Using a lookup helps you avoid specifying the same options multiple times when configuring forms. To view all configured lookups, click the **Settings** link in the navigation menu. In the Settings navigation menu, open the “Forms” group, then click the **Lookups** link. You will then arrive at the Lookups list.



NAME	OPTIONS
Location Type	Country, Region, Province, District, Governorate, Chiefdom, State, City, County, Camp, Site, Village, Zone, Sub Distr...
Reporting Location Type	Province, District
Country	Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Australia, Austria, Azerbaj...
Nationality	Nationality1, Nationality2, Nationality3, Nationality4, Nationality5, Nationality6, Nationality7, Nationality8, Nationality9...
Ethnicity	Ethnicity1, Ethnicity2, Ethnicity3, Ethnicity4, Ethnicity5, Ethnicity6, Ethnicity7, Ethnicity8, Ethnicity9, Ethnicity10

Creating a Lookup

To create a new lookup, click the New button at the top of the page.



ENGLISH TEXT	ENABLED?
Option 1	☐
Option 2	☐

Specify a name for the Lookup you are creating, then use the **Add** button to add options. To add translations for the Lookup name or options, select a language in the “Language” dropdown at the top of the page, then fill in the translation text.

Language
العربية
English Text *
Case Status
Translation Text *
إوضاع الحالة

Options
+ ADD

	ENGLISH TEXT	TRANSLATION TEXT	ENABLED?
⋮	Open	مفتوحة	☒
⋮	Closed	مغلقة	☒

Editing a Lookup

To edit an existing Lookup, go to the Lookups list, click on the Lookup you would like to edit, then, on the Show Lookup page, click **Edit**.

LOOKUP CASE STATUS
EDIT

Language
English
English Text *
Case Status

Options

	ENGLISH TEXT	ENABLED?
⋮	Open	☒

To rearrange the Lookup options, use the “grip” on the left side of the option row to

Options		
	ENGLISH TEXT	ENABLED?
	Open	☒
	Closed	☒
	Transferred	☒
	Duplicate	☒

drag-and-drop an option into a new position.

Note that you cannot delete options from a Lookup. Instead, you can “disable” an option. This will prevent users from selecting this option in the future. To do this, un-check the box next to the option in the “Enabled?” column of the Options list.

Options		
	ENGLISH TEXT	ENABLED?
	Open	☒
	Closed	☒
	Transferred	☐
	Duplicate	☒

Remember to click the **Save** button after you have finished making changes.

Managing Form Groups

As you scroll through the list of lookups, you will notice that there is a lookup for the form groups for each type of record. In CPIMS+, Find the lookup labelled "Form Groups - CP Case" you will see that the options include all of the Form Groups see when viewing a CP Case.

Tracing Status	Open, Tracing in Progress, Verified, Reunified, Closed
Form Groups - CP Case	Record Information, Approvals, Case Conference Details, Identification / Registration, Data Confidentiality, Review S...
Form Groups - CP Tracing	Record Owner, Inquirer, Traces, Photos and Audio, Other Reportable Fields, Record Information

In GBVIMS+, find the lookup labelled “Form Groups - GBV Case” you will see the options include all the Forms Groups see when viewing a GBV Case.

Form Groups - GBV Case	Record Information, Consent For Services, Documents, Consent For Referrals, Safety Plan, Action Plan, Survivor Assessment, Case Closure, Client Feedback, Identificatio...
Form Groups - GBV Incident	GBV Individual Details, Incident, Type of Violence, Record Owner, Alleged Perpetrator, Service Referral, Other Reportable Fields, Record Information

To update or provide translations for the Form Groups, find the lookup that corresponds to the Module and Record Type of the Form Groups you want to update, click into the Lookup, and click **Edit**. You can now add, update, translate, and reorder the Form Groups the same way you would manage the options for any other Lookup.

Other Important Lookups

There are other Lookups which impact key Primero functionality. Here are a few of them:

- **Service Type** - Updating these options will affect which services you can configure for Agencies and Users, as well as which options appear when you are selecting a type of Service for a Referral.
- **Service Response Type** - Since some implementations use a Case’s most recent Service Response Type as its workflow status, updating the **Service Response Type** Lookup may affect which Workflow Statuses appear on the Case and in the Dashboards.
- **PDF Header** - These options appear for users choosing which header to show at the top of their PDF exports. The default values are currently PDF Header 1, PDF Header 2, PDF Header 3 which should be updated to headers agreed by the partners.

Lookups

PDF Header	PDF Header 1, PDF Header 2, PDF Header 3
------------	--

- **Agency Office** - Users can be assigned to one of these “Agency Offices.” Supervisors will then be able to filter records by which Agency Office’s users created them.

Locations

To view all Locations currently configured in the system, click the **Settings** link in the navigation menu. Then, in the Settings navigation menu, click **Locations**. You will see a list of all system locations.

SETTINGS

LOCATIONS

Users

Roles

User Groups

Agencies

Forms

Forms

Lookups

Locations

Contact Information

NAME	CODE	ADMIN LEVEL	TYPE	HIERARCHY
Country 1	XX	0	Country	
Province 1	XX01	1	Province	XX
District 1	XX0101	2	District	XX, XX01
District 2	XX0102	2	District	XX, XX01

APPLY

CLEAR


Enabled / Disabled

Rows per page: 20

1-4 of 4

Importing Locations

To import locations, click the Actions menu at the top-right of the screen, then click the **Import** action.



The Import Locations modal will appear. Here, you can upload the CSV file containing your Locations. Select your file, then click **Import** to begin creating Locations.

Formatting the Locations File

The CSV file containing your locations must be precisely formatted for your Locations to be created properly.

- **UTF-8:** Your file must be encoded using UTF-8. To do this in Microsoft Excel, click "Save As." In the "Save as type" dropdown, select "CSV UTF-8 (Comma delimited) (*.csv)".
- **HXL headers:** The second row of your file should contain HXL tags which indicate the Location attribute contained in that column. This tag should contain a designation for both the Location admin level and the Location attribute.
 - The highest admin level should be represented by the HXL hashtag "#country"
 - Each admin level must contain at least the attributes "name", and "code".
 - If Locations will need their names translated into languages other than English, include an extra column for each admin level to specify the name in that language.
 - For a full reference of HXL tags and how to format them, please see the HXL dictionary: <https://hxlstandard.org/standard/1-1final/dictionary/>
- **All admin levels represented in each row:** Each row must contain not just the attributes for that location, but for its parent locations.

Below is a sample of the first few rows of a properly-formatted Location CSV file containing place name translations for Jordanian Arabic. **Note:** we strongly suggest uploading 10,000 locations at a maximum in order to not impact performance. Click here to download a template for both CPIMS+ and GBVIMS+:

<https://drive.google.com/file/d/1qHYUs9hgZJ0luHPJi6l2-VExulnfH65U/view?usp=sharing>

Country Code	Country Name	Country Name (Jordanian Arabic)	Governorate Code	Governorate Name	Governorate Name (Jordanian Arabic)	District Code	District Name	District Name (Jordanian Arabic)
#country+code	#country+name	#country+name+ar-JO	#admin1+code	#admin1+name	#admin1+name+ar-JO	#admin2+code	#admin2+name	#admin2+name+ar-JO
JOR	Jordan	الأردن						
JOR	Jordan	الأردن	JOR005	Amman	عمّان			
JOR	Jordan	الأردن	JOR005	Amman	عمّان	JOR005009	Wadi Essier	وادي السير
JOR	Jordan	الأردن	JOR006	Tafiela	الطفيلة			
JOR	Jordan	الأردن	JOR006	Tafiela	الطفيلة	JOR006001	Hasa	الحسا

GBVIMS+ Locations for the IR Exporter

You can find a sample of the GBVIMS+ locations uploader here:

<https://drive.google.com/file/d/1qHYUs9hgZJ0luHPJi6l2-VExulnfH65U/view?usp=sharing>

please watch this video to show you how to upload the locations for the GBVIMS+:

<https://youtu.be/VYFm-cwikv0?si=iwLkMFZC1R4zf7h>

The system settings must be updated to be aligned to the locations uploaded into the system for GBVIMS+ IR Export. The types should be: Country = admin 0, County = admin 1, District = admin 2. Admin 3 is not included in the IR export.

Updating Locations

Administrators can enable and disable Locations but we recommend the locations that are uploaded must be the final list. When an administrator disables a location, users will then see that location act like a disabled option whenever they are creating or editing a record and using a location field.

When an administrator enables a location, users should then see that location act like a normal, enabled option whenever they are creating or editing a record and using a location field.

When a user is editing a record where a location was saved in a field, but the location is now disabled, the user will still see the fully-translated location value in the field, but if they de-select that value, they cannot re-select it.

When a user is creating a record or editing a record and clicking into a location field with no previously-selected value, they will not see disabled locations as valued.

Updating Location Labels

If you would like to update the location labels to another label, Primero has the following labels available and would need to be updated by a Primero team developer:

Admin Level	Key	EN	FR	AR
0		Country		
1	departement_fr	Département	Département	--
1	region_fr	Région	Région	--
1	county			
1	wilaya	Wilaya	Wilaya	ولاية
2	commune	Commune	Commune	
2	division_fr	Division	Département	
2	prefecture	Prefecture	Préfecture	
2	district			
2	cercle			
2	moughataa	Moughataa	Moughataa	مقطعة
3				
3	sub_division	Sub-division	Commune	
3	sub-prefecture	Sub-prefecture	Sous-préfecture	

To implement this, for Département (en), for example, then:

1) Update the system settings:

```
ss=SystemSettings.current
```

```
ss["reporting_location_config"]["admin_level_map"]["1"]=['departement_fr']
```

```
ss["reporting_location_config"]["admin_level_map"]["2"]=['commune']
```

```
ss.save!
```

2) Restart the app pod

Using the Locations

There are many different areas where locations are used within Primero. The below guidance lists the various ways locations are configured and used in the system. Firstly, note that the locations of case workers or managers are selected on their user profile:

The screenshot shows a user profile form for 'Janani Panchalingam'. The 'Location' field is highlighted with a red border and contains the text 'Colombia: Amazonas: El Encanto'. Below the 'Location' field are checkboxes for 'Disabled' and 'Receive email notifications?'.


In this example, the location selected is “Colombia: Amazonas: El Encanto”. “El Encanto” is the **district** location, which is administrative level 2.

If the location selected was “Colombia: Amazonas”, this is **county** or **province** location, which is administrative level 1.

If the location selected was “Colombia”, this is **country** location, which is administrative level 0.


Locations that appear on the Dashboard

When logging in as a system administrator or some managers, you are able to see the cases by a particular administrative level. This is initially set by the developers when the system is set up. In the example below, the system administrator sees the number of **registered cases by district** and this district is determined by the location selected in the case worker's profile:



DISTRICT	OPEN CASES	NEW (LAST WEEK)	NEW (THIS WEEK)	CLOSED (LAST WEEK)	CLOSED (THIS WEEK)
Medellin	3	0	0	0	0
Lima	2	0	0	0	0
Ipiales	1	0	0	0	0
Acevedo	1	0	0	0	0

If a user would like to view the “Cases by Locations” dashboard in a different level from *district* you are to set the location level that appears on the dashboard on the role itself by selecting the level on the question “What location type should be used for reporting for this role?”:



Settings

Role CP Case Management Supervisor Cancel Save

Name *
CP Case Management Supervisor

Description

☐ Disabled

☒ Is Manager?

☐ Can this role be used for external transfers?

☐ Can this role be used for external Referrals?

Modules
CP

What records does this role affect?
Access all records or users in my group

What location type should be used for reporting for this role?
District

If you select “District” or “Province” then the cases will display by that particular level on the dashboard. **Please note that if a user’s location in their user profile is set to “Colombia”, then they will not appear in the dashboard because there is no country level dashboard. You will need to ensure all users have the most specific location, such as “Colombia: Amazonas: El Encanto”, to be able to appear in both the District and Province dashboard. Users who have “Colombia: Amazonas” will not appear in the District dashboard because the location is not specific enough in their user profile.**

If you would like the dashboard to not display registered cases by district, the dashboard can be updated by a developer to display cases by current location. Read more about current location in the next section.

Current Location Filter

When you are on the case list view, you can filter by “Current Location”:

The screenshot shows a dashboard titled "Cases" with a table of cases and a sidebar of filters. The table has columns for checkboxes, case IDs, ages, genders, dates, times, and case workers. The sidebar contains filters for Assessment, Closure, Action Plan, Case Closure, Protection Concerns, Displacement Status, Current Location, Agency Office (GBV field), User Groups, and District. The "Current Location" filter is highlighted with a red box and shows a dropdown menu with the selected value "Colombia Amazonas El Encanto".

	Case ID	Age	Gender	Date	Time	Case Worker
☐	767234f	*****		25-Jan-2023	2023 10:51	kpi.cw2
☐	cdf021e	43	Female	24-Jan-2023	2023 16:51	kpi.cw
☐	1892c56	24	Female	24-Jan-2023	2023 16:43	kpi.cw
☐	84a6107	16	Female	24-Jan-2023	2023 16:32	kpi.cw

Rows per page 20 1-20 of 77

Filters:

- Assessment
- Closure
- Action Plan
- Case Closure
- Protection Concerns
- Displacement Status
- Current Location** (Colombia Amazonas El Encanto)
- Agency Office (GBV field)
- User Groups
- District

This field is the child’s current location and typically on the Care Arrangements form or the Child’s Details form under the field called “Current Location” for CPIMS+ only.

District Filter

When you are on the case list view you can filter by “district” which filters for cases by the case worker’s district set on their user profile:

Cases + New

Case ID	Age	Gender	Date	Time	Location
☐ 1892c56 *****	24	Female	24-Jan-2023	16:43	kpi.cw
☐ 84a6107 *****	16	Female	24-Jan-2023	16:32	kpi.cw

Rows per page 20 1-20 of 77

- Action Plan
- Case Closure
- Protection Concerns
- Displacement Status
- Current Location
- Agency Office (GBV field)
- User Groups
- District
 - El Encanto
- By Date
- Photo

Agency Office (GBV field) Filter

In GBVIMS+, when you are on the case list view, you can filter by “Agency Office (GBV field)”:

Cases + New

Current Location

Agency Office (GBV field)

- ☒ Cundinamarca
- ☐ Medellin
- ☐ Ipiales
- ☐ Cucuta
- ☐ Los Palos
- ☐ Bogota

User Groups

District

By Date

Photo

[Less...](#)

This is set by the Agency Office selected on the user’s profile and note that this is not the same as the Agency nor does it have a formal link to the Agency in the system:

Settings

Users Jan Panchalingam

CancelSave

Email *

jpanchalingam@primero.org

Agency *

UNICEF

Agency Office (GBV field)

Position

Location *

☐ Disabled

☒ Receive email notifications?

If you would like to update the list of agency office (GBV field) options, you can update them in the lookup called “Agency Office”:

Settings	Lookups	+ New
	Agency Office	Cundinamarca, Medellin, Ipiales, Cucuta, Los Patios, Bogota, Puerto Santander, Villa del Rosario, Nariño, Quito, Machala, Tulc...

Locations that appear on the reports

Within the reports you are able to generate reports based on the locations listed below:

Other Reportable Fields

Case Manager's Location

Case Manager's Location (Province)

Case Manager's Location (District)

Location of previous record owner

Location of previous record owner (Province)

Location of previous record owner (District)

We also are able to generate a report by:

- Created-by user
- Owned-by user
- Created-by user groups
- Owned-by user groups

Note that "Case Manager's Location" refers to the "Case Worker's Location" or "Record Owner's Location", *not* the supervisor of the case worker.

Locations when making a referral or transfer

Once a location is selected in an internal **referral** or an internal **transfer**, the users list will be filtered by the province or district of the user. Therefore, if a user is not able to find a specific user, please check their user profile location as well as their agency to ensure the user is correctly set up.

The image displays two overlapping screenshots of a web application interface. The left screenshot shows a modal titled "SERVICES" with a red rectangular highlight around three input fields: "Implementing Agency" (set to "International Rescue Committee_Colombia"), "Service delivery location" (set to "Colombia: Amazonas: El Encanto"), and "Service provider name" (set to "irc-cw-015"). Below these is a "Referred?" checkbox with "Yes" selected. The right screenshot shows a modal titled "TRANSFER CASE EFAB95F". It contains two checkboxes: "Are you transferring to a remote system?" and "Do you have consent from the individual to make this transfer?". Below these are three dropdown menus: "Agency" (set to "International Rescue Committee_Peru"), "Location" (set to "Colombia: Amazonas: El Encanto"), and "Recipient" (empty). There is a "Notes" text area and two buttons at the bottom: "Transfer" (with a checkmark icon) and "Cancel" (with an 'X' icon).

Components of User Management

As described above, each Primero user must have one role and at least one user group, allowing them to access the functions and records necessary to perform their day-to-day work. User management consists of the following three elements:

- **Users** are the individuals using Primero who each have a unique username and password. Each user is given access to one or more modules in Primero (e.g., CP for case management or GBV for gender-based violence case management).
- Their **Role** sets which actions they can perform on which record types; as well as which records they are able to access. Below are some examples to illustrate these two concepts:
 - *Actions:* A role may be able to "View," "Edit," and "Flag" Cases, but only "View" Incidents.
 - *Access:* A may be able to access all records in the system, all records managed within their User Groups, all records managed by their Agency, or only their own records.
- A **User Group** is like a team of users. Managers within a User Group will be able to see any records managed by members of the group.
- A user's **Agency** represents the actual organization they work for. Please note that, while User Groups are not linked to Agencies in any way, an administrator can create multiple User Groups which represent teams within an Agency (example: all Save the Children case workers in District 5). Or, they may create a User Group which spans multiple Agencies (example: all Alternative Care service providers in Camp 1).

Creating and Editing Roles

In the Settings navigation menu, click **Roles**. To create a new role, click the New button, or to edit an existing Role, click a Role in the list, then click the Edit button on the Show Role page.

General Settings

In the first section of the new/edit Role page, you will see the below fields

The screenshot shows the 'General Settings' form for a role. It includes the following fields and options:

- Name ***: A text input field containing 'Agency User Administrator'.
- Description**: A text input field.
- Disabled**: A checkbox, currently unchecked.
- Is Manager?**: A checkbox, currently checked.
- Can this role be used for external transfers?**: A checkbox, currently unchecked.
- Can this role be used for external Referrals?**: A checkbox, currently unchecked.
- Modules**: A section with a tag 'CP' and a dropdown arrow.
- What records does this role affect?**: A dropdown menu with the selected option 'Access all records or users in my group'.
- What location type should be used for reporting for this role?**: A dropdown menu with the selected option 'Province'.

- **Name:** The name of the role. For example, GBV Case Worker.
- **Description:** A written description of the role and its function.
- **Disabled:** Since you cannot delete Roles in Primero, disabling a Role prevents it from appearing as an option when an administrator creates a User.
- **Is Manager?:** This setting allows Users with this Role to see management-related features such as the “By Caseworker” filter on the Cases list. You should generally select this setting for all managerial and administrative Roles.
- **Can be used for external Transfers?:** Allows this role to appear as an option when a user is selecting the *Type of Recipient* for an external transfer. When a user selects the *Type of Recipient*, the external transfer will only include information that the selected *Type of Recipient* would normally have access to in Primero. For instance, if the user selects “Service Provider” as their *Type of Recipient*, and the Service Provider role only has access to the “Child’s Details” form, the external transfer will only include information contained in this form.
- **Can be used for external Referrals?:** Allows this role to appear as an option when a user is selecting the *Type of Recipient* for an external transfer. When a user selects the *Type of Recipient*, the external referral’s PDF export file will only include information that the selected *Type of Recipient* would normally have access to in Primero. For instance, if the


user selects "Service Provider" as their *Type of Recipient*, and the Service Provider role only has access to the "Child's Details" form, the external referrals's PDF export file will only include information contained in this form (if CPIMS+) or "Survivor Assessment" (if GBVIMS+).

- **Can this role be used for the "Type of Referral" dropdown?:** This allows the role to appear as an option for the "Type of Referral" dropdown when the user performs an internal referral. If the user chooses this role as a type of referral, the referral recipient will only be able to access the forms which the selected role can access in the "Forms" section of the role.
- **Modules:** Which Primero modules will users with this Role have access to? Typically, Roles only have access to one. For instance, a CP Case Worker would only have access to the CP module. This impacts which forms are available when a User with this Role is creating, viewing, or editing a record such as a Case. For GBVIMS+, a GBV Case Worker would only have access to the GBV module. This impacts which forms are available when a User with this Role is creating, viewing, or editing a record such as a Case.
Please ensure this field has a module selected. Note: you must have a module selected to be able to "copy" a role.
- **What records does this role affect?:** This controls which records Users with this Role will be able to access.
 - This setting has the following options:
 - "Access only my records or user"
 - "Access all records or users in my group"
 - "Access all records or users in my agency"
 - "Access all records or users"
 - "No records - Admin functionality only."
 - Please note that a User will be able to perform their permitted actions for a given type of record for any records of that type which they can access. For instance, if a supervisor role has the *Edit* permission on *Cases*, and they have access to *all records in their group*, they will be able to *edit all Cases in their groups*.
- **What location type should be used for reporting for this role?:** Primero generally uses a system-wide setting for the level of specificity used to report Cases' locations in Dashboards and filters. Let's use Ghana as an example and assume that usually locations in Ghana are classified into one of Ghana's 260 districts. If a user is looking at the "Cases by Location" dashboard, and only has access to the Cases in their own region, they will only see a few rows in the dashboard - one for each district in their region. In this case, classifying locations by district makes sense. However, a national administrator, with access to all cases in the system, would see 260 rows in that same dashboard. This is confusing and impractical. In this situation, the National Administrator role should have the "What location type should be used for reporting for this role?" field set to "Region," so that National Administrators only see 16 rows in the dashboard: one for each of Ghana's 16 regions.

Permissions

Scrolling down the page, you will see that a Role's "Permissions" are organized by record type. This includes both the three main record types (Cases, Incidents, and Tracing Requests), as well as record types like "User" and "Report" which pertain to system configuration, and which usually only administrators can access.

Please note that you can expand or collapse the section for a particular resource type by clicking on the header of that section. This makes scrolling through the page easier.



The screenshot displays a web interface for managing permissions. At the top, there is a list of record types, each with a dropdown arrow: 'Case', 'Incident', 'Tracing Request', 'Potential Match', and 'Roles'. Below this list, the 'Users' section is expanded, showing a list of permissions with checkboxes. The permissions listed are: 'Create' (checked), 'View' (checked), 'View (Within Agency)' (unchecked), 'Edit' (checked), and 'Manage (all permissions for this resource type)' (unchecked).


Record Type	Permissions
Case	
Incident	
Tracing Request	
Potential Match	
Roles	
Users	☒ Create ☒ View ☐ View (Within Agency) ☒ Edit ☐ Manage (all permissions for this resource type)

You can update permissions for the following record types:

- **Case:** Represents an individual child, survivor, or other beneficiary.
- **Incident:** Represents an occurrence of GBV which has occurred to the survivor. Incidents should always be linked to Cases. These are usually incidents of abuse or violence, though they can also correspond to events like encounters with law enforcement. Incidents are often linked to Cases.
- **Tracing Request:** Represents an individual trying to locate and reunify with an unaccompanied or separated Case.
- **Potential Match:** Represents the link between a Tracing Request and a Case. Access to Potential Matches is necessary for Family Tracing and Reunification (FTR) work.
- **Role:** Dictates which actions a User can perform in Primero.
- **User:** Represents an individual User account.
- **User Group:** Represents a team or a collaborative group of users who can share information. Managers can typically see all of the records managed by social workers in their User Groups.


- **Agency:** Represents an organization with members who use Primero. Agencies exist independently of User Groups.
- **Forms, Lookups:** Controls the ability to configure Primero Forms and Fields, as well as Lookup options used within them.
- **System:** Miscellaneous system-wide configuration settings.
- **Report:** Aggregate data analysis tool. Includes table and graph representations of data.
- **Dashboard:** Dictates which summary information appears on the home page.
- **Audit Log:** Filterable list of all actions performed in the system. Does not include any identifiable information on Cases, Incidents, or Tracing Requests.
- **Matching Configuration:** Controls which fields are used to compare Tracing Requests with Cases during Family Tracing and Reunification.
- **Duplicate Search:** Advanced case search for administrators.
- **Pulse / KPIs:** A set of performance-monitoring indicators and dashboards tailored for GBV programming.

Each resource type has a different set of permissions, each of which represents a specific action that a User with this Role can perform. To see an explanation for a permission, hover your mouse over the text for that permission. A box will appear with a short description. **When in doubt, always check these explanations for guidance on how to configure a Role.**



A few specific permissions warrant explanation here:

- **Roles - "Other roles managed by this role":** This specifies which other Roles users with this Role can access. For example, if you give this Role the ability to 'View' and 'Edit' Roles, they will only be able to view or edit the Roles you select here. For example, to limit what kinds of Users an Organizational Administrator can create, you would give them the "View" and "Assign" permission on Roles, but you could select the "Case Worker" and "Supervisor" Roles in this field to specify that Organizational Administrators can only create users with these two Roles. This prevents the Organizational Administrator from creating a user account with a very powerful Role such as "National Administrator."



- **Dashboard - “Tasks Page”:** Rather than controlling access to a specific “dashboard” within the home page, this permission gives Users with the Role access to the separate “Tasks” page, where users can keep track of upcoming case management deadlines. For more information on this view, see the [Primero CPIMS+ User Guide](#) or [Primero GBVIMS+ User Guide](#).
- **Users - “View (Within Agency)”:** This denotes that the given role can perform actions on Users only within the current User's agency. As an example, suppose an administrator named Ahmad at a local NGO named "ABC" needs to be able to manage the organization's Users: resetting passwords, disabling Users, and creating new User accounts. Ahmad's User account gets a role with the “Edit,” “Assign,” and “View (Within Agency)” permission for Users. Because of this, Ahmad will only be able to view and edit User accounts which, like Ahmad's User account, have their agency set to "ABC." This means Ahmad can only access, and is only responsible for, Users within his organization.
- **Reports - “Group Read”:** Typically, when a User views a Report, the numbers they see will reflect all records in the system, *regardless of which records that User actually has access to*. For instance, a User with no access to Cases can still view a Report which includes information about all Cases in the system. However, Users whose Role has the “Group Read” permission on Reports will see numbers in each report will reflect *only those records which are accessible to users in the current user's user groups*. This permission is often used for local, regional, or agency administrators.
- **(Multiple resource types) - “Manage”** - The “Manage” permission appears on multiple types of resources and generally means “All of the above.” If a Role is given the “Manage” permission on a resource, it will be able to perform **all available actions** on that resource.

Action Needed Dashboards by Role

Below you will be able to see how to configure a roles so that they see one or more of the new **Action Needed** dashboard elements.

Case Workers and Service Providers

We suggest you turn on these dashboard permissions

- Action Needed: New or Updated
- Action Needed: New Referrals
 - *Only if the role can receive referrals*
- Action Needed: Transfers Awaiting Acceptance
 - *Only if the role can receive transfers*

Managers / Supervisors

We suggest you turn on these dashboard permissions

- Action Needed: New or Updated
 - *Only if managers / supervisors sometimes manage their own cases.*
- Action Needed: New Referrals
 - *Only if the role can receive referrals*
- Action Needed: Transfers Awaiting Acceptance
 - *Only if the role can receive transfers*

Administrators

We suggest you turn on these dashboard permissions

- Action Needed: Transfers Awaiting Acceptance
 - *Only if the role can receive transfers*

Form Access

Scrolling down the page, you will arrive at the “Forms” section. Here, you specify which forms this Role will have access to for each of the three main record types: Cases, Incidents, and Tracing Requests.

Forms - Case ^			
	Hide	Show	Show and Edit
Approvals	☐	☐	☒
Assessment	☐	☒	☐
Assessment Status	☐	☐	☒
Child's Details	☐	☐	☒
BID Status	☒	☐	☐

This dictates which information a Role can access and modify. For instance, Roles with the “Show and Edit” permission on Cases, and with access to the “Child’s Details” form will be able to edit information for any field contained in this form. Roles with “Hide” permission, will not be able to view the “BID Status” form. Roles with “Show” permission will be able to view but cannot edit the “Assessment” form.

Please note that you can expand or collapse the sections for each record type (e.g. “Forms - Case”) within the Forms section by clicking on the header of the section.

Other restrictions on administrative Roles

Superusers and User Admins

There are two important types of roles which we must discuss here, since the system treats them differently. The first is the **Superuser** role.

A **Superuser** role is a role has the all-encompassing "manage" permission for **Cases, Incidents, Reports, Roles, Users, User Groups, Agencies, System Settings, and Forms and Lookups**. A superuser, meanwhile, is a user who has been assigned such a role. Since this user has a great deal of power within the system, only superusers can view or edit the attributes of other superusers. For similar reasons, superuser roles cannot be edited within Primero's administrative interface.

The second special type of role is the **User Admin** role. A user admin role has less power than a superuser role, but is defined as having the all-encompassing "manage" permission for **Roles, Users, User Groups, Agencies, System Settings, and Forms and Lookups**. Once again, a user admin *user* is a user who has a user admin *role*. Only superusers and other admin users can view or edit the attributes of user admin users. Similarly, only superusers can edit a user admin role.

Please note that Superusers are never enabled except for situations of emergency maintenance and support.

Note: As a security measure, admins will not be able to access roles they create and the Primero team will need to provision the access to any newly created roles. If the programme team does not agree with this security measure, the Primero team can remove the role access permission so this does not become an impediment in the programme.

User Groups


User Groups are teams of users. Users within this group with managerial Roles will be able to access all the records managed by the other users in the group. As with Roles, User Groups

should be created before you create individual users. As we discussed in the **Creating and Editing Roles** section, each role has one of the following “access” levels:


- Access only my records or user
- Access all records or users in my group
- Access all records or users in my Agency
- Access all records or users
- No access - Admin functionality only

The actions the user can perform once they have access to a record are driven by the privileges set with their role. These permissions given to a user apply to all records they have access to. If a user has the “Edit” permission on Cases, and also happens to have access to the Cases of all the Users in their User Group, then they will also be able to edit the Cases of all the Users in their User group.

The following diagram helps explain the relationship between Users, Roles, and User Groups through a hypothetical Role/User Group setup, where the different roles are given specific permissions regarding their ability to see records within different User Groups:



To see the User Groups currently configured in your system, click the **Settings** link in the navigation menu, then click the **User Groups** link in the Settings navigation menu. You will arrive at the User Groups list.



Limited Access to User Groups

Note that, local administrators who manage the User accounts for their team will only see User Groups in this list *which they are part of*. Similarly, when this local administrator creates or updates a User account, they will only be able to assign a User to the User Groups that the local administrator is part of. This specifically applies to Users whose Roles have the “All records or users in my group” access level.

For example, imagine a User with the “Camp Supervisor” Role manages User accounts for all the User Groups in Camp 1. The “Camp Supervisor” Role would have the “All records or users in my group” access level, and this Supervisor User would be part of all the User Groups for Users in Camp 1 (for example: “Camp 1 Block 1,” “Camp 1 Block 2,” and “Camp 1 Block 3”). When this supervisor goes to the User Groups list, they would only see these three User Groups, and when they created a User account, they would only be able to assign the User to one of these three User Groups.

Creating and Editing User Groups

To edit a user group, click one in the list. Once you have reached the Show User Group page, click the **Edit** button. Make changes, then click **Save**.

To create a new user group, click the **New** button at the top of the User Groups List page. Specify a Name and Description, then click **Save**.

Please note that User Groups cannot be deleted. To prevent a User Group from being assigned to Users in the future, or to prevent it from appearing in filters, dashboards, or Reports, edit the User Group and check the “**Disabled?**” tick box.

Settings

Users

Roles

User Groups

Agencies

Forms

Locations

User Groups Primero CP

✕ Cancel

✓ Save

Name *

Primero CP

☐ Disabled

Description

Default Primero User Group for CP

Agencies associated with this User Group

You can add “Agencies associated with this user group”. This will not impact any specific functionality. It will allow you to filter by agency in the “User Group” list view:

Settings

Users

Roles

User Groups

Agencies

Forms

Locations

Contact Information

Code of Conduct

Configurations

Audit Logs

User Groups

+ New

Apply

Clear

Enabled / Disabled

Enabled

Disabled

Agency

International Rescue Committee

UNICEF


TRI Agency-DNM

Save the Children

Name	Description
Primero CP	Default Primero User Group for CP
Primero FTR	Default Primero User Group for FTR
Kristy Test Group - Greatest User Group Ever	testing
Seattle	Kristy's Supervision Group - Oct 4 2020
Jordan	
Technical group	discussing high risk cases
Site A	This is a user group for Site A caseworkers. These caseworkers are supervised by Gloria.
Site A	This user groups covers Site A, which has one supervisor and three caseworkers.
Save the Children Social Workers	
Clinic Service Providers	

Agencies

Agencies represent the actual organizations using Primero. You must set up Agencies before creating User accounts. To view the Agencies currently configured in your system, click the **Settings** link in the navigation menu, then click the **Agencies** link in the Settings navigation menu. You will arrive at the Agencies List page.



Please note that Agency Administrators, whose Roles have the “View (Within Agency)” permission on Users, will only see their own Agency in this list. Similarly, when they are creating new User accounts, they will only be able to assign a User to their own Agency. For more information on this restriction, please see the **Permissions** section under **Creating and Editing Roles**.

Creating and Editing Agencies

To edit an existing Agency, click the Agency in the list. Then, on the Show Agency page, click **Edit**.

To create a new Agency, click the **New** button at the top of the Agencies List page.

Agency Logos

You can configure an Agency with logo images. If you would like to have the logo appear, you must upload two images:

- An “**Icon**” logo with square proportions. This appears on phone and tablet screens.
- A “**Large**” logo with wide, short, rectangular proportions. This appears on large screen sizes and in PDF exports.

Icon Logo
This will appear on small screen sizes, tablets, and phones. This should be a square.

SELECT FILE



Large Logo
This will appear on large screen sizes and in PDF exports. This should be a rectangle, with the length longer than the height.

SELECT FILE

unicef 

☒ Display this agency's logo in Primero?
Display this agency's logo in Primero?

☐ Make logo available for PDF exports?
Note: user's Agency logos are available to them by default, so you only check this if you want this logo to be available to all users.

☐ Exclude this agency from lookups and filters

In addition to specifying which images to use for an Agency's logo, you can choose where these logos appear using the below settings:

- **Display this agency's logo in Primero?** - Checking this box will make the Agency logo appear in the navigation menu and on the Login page.
- **Make logo available for PDF exports?** - If this box is checked, users performing PDF exports will be able to select this Agency's logo to appear in the export file's header.
- **Exclude this agency from lookups and filters** - This setting is for Agencies which do not have any Users in Primero. For instance, if you would like to display the logo of your country's Ministry of Justice in the navigation menu or in PDF exports, but no Ministry of Justice staff will actually use Primero, you can create a "Ministry of Justice" Agency, configure its logos, then check this box to ensure that Users do not accidentally select "Ministry of Justice" as the Agency for a referral or transfer.

Agency Services

Each Agency can be configured with a list of Services it provides. The options which appear here come from the **Service Type** Lookup.

Agency Services

Basic psychosocial care ✕ Focused non-specialized MHPSS ✕ Non-formal education ✕

Alternative care

Security (e.g. safe shelter)

Education (formal)


Family tracing and reunification

Specialized MHPSS care

Food


Specifying services for your Agency is very important for controlling the Service and Referral workflow in Primero, as explained below:

- When a user adds a Service to their Case, they will first specify the **Type of Service**.



The screenshot shows a modal window titled "SERVICES" with a close button (X) in the top right corner. Inside the modal, there are several fields. The "Type of Response" field is set to "Service provision". Below it, the "Type of Service" field is active, with the text "alt" entered. A dropdown menu is open, showing two options: "Alternative care" (highlighted) and "Sexual and reproductive health". At the bottom, the "Type of referral" field is visible.

- Once the user has selected the Service, they will choose an Agency to provide the Service. Primero will only let the user select an Agency which has been configured to provide that Type of Service. So, if the user has selected “Alternative Care” as their Type of Service, and Save the Children is configured to provide “Alternative Care” Services, then Save the Children will appear as an option for the **Implementing Agency** field. Other Agencies, which are not configured to provide “Alternative Care” services, will not even appear as options.



The screenshot shows the same "SERVICES" modal window. The "Implementing Agency" field is now active, showing a dropdown menu with the text "(Select...)". The dropdown menu is open, showing two options: "MSF" and "Save the Children" (highlighted). Below this, the "Service product name" field is visible, also showing a dropdown menu with the text "(Select...)". At the bottom, the "Referred?" field is visible, with a checkbox labeled "Yes".

- Once a user has selected a Service Type and an Agency, they can select a User to perform the service. Primero will only show Users who are part of the selected **Implementing Agency**, and which are configured to provide the selected **Type of Service**.
 - While we will discuss how to configure which Services a User can provide in the [Creating and Editing Users](#) section of this guide, it is important to know that an Agency’s configured Services can impact which services a User provides. If an administrator, creating a User account, does not specify which Services the User can provide, *Primero will automatically configure that User to be able to provide the Services of their agency*. So, for instance, if Save the Children is configured to provide “Alternative Care” and “Food” services, and an administrator creates a Save the Children User without specifying a list of Services for that User, Primero

will automatically configure that User to be able to provide “Alternative Care” and “Food” Services.

Once you are done making changes, please remember to click the **Save** button at the top of the page.

Note: Once an agency has been created, it cannot be deleted. The agency can only be disabled. To do this, edit the Agency, check the “**Disabled?**” tick box, then save.

Users

To see all users currently in the system, click on the **Settings** link in the navigation bar, then click the **Users** link in the Settings navigation menu. You will now arrive at the Users List page. You can filter users by Agency, User Group, and whether or not they are Enabled, using the filters panel on the right side of the page.

The screenshot shows the 'USERS' page in a system. On the left is a sidebar with 'SETTINGS' and 'USERS' tabs. Under 'USERS', there's a list of links: Users, Roles, User Groups, Agencies, Forms, Locations, Contact Information, Configurations, and Audit Logs. The main area displays a table of users with columns: FULL NAME, USERNAME, POSITION, and AGENCY. The table lists 10 users, including ASANTE AKIM CENTRAL MUNICIPAL ASSEMBLY CASE WORKER 1 and 2, ASANTE AKIM CENTRAL MUNICIPAL ASSEMBLY MANAGER, ADANSI ASOKWA DISTRICT ASSEMBLY CASE WORKER 1 and 2, ADANSI ASOKWA DISTRICT ASSEMBLY MANAGER, and ABURA-ASEBU-KWAMANKESI DISTRICT ASSEMBLY CASE WORKER 1 and 2. On the right, there's a filter panel with a '+ NEW' button at the top. Below it are filters for 'Enabled / Disabled' (with an 'APPLY' button highlighted by a red box), 'Agency' (with a dropdown menu showing 'UNICEF' highlighted by a red box), and 'User Group'.

FULL NAME	USERNAME	POSITION	AGENCY
ASANTE AKIM CENTRAL MUNICIPAL ASSEMBLY CASE WORKER 1	aacma-cw-1		
ASANTE AKIM CENTRAL MUNICIPAL ASSEMBLY CASE WORKER 2	aacma-cw-2		
ASANTE AKIM CENTRAL MUNICIPAL ASSEMBLY MANAGER	aacma-mgr		
ADANSI ASOKWA DISTRICT ASSEMBLY CASE WORKER 1	aada-cw-1		
ADANSI ASOKWA DISTRICT ASSEMBLY CASE WORKER 2	aada-cw-2		
ADANSI ASOKWA DISTRICT ASSEMBLY MANAGER	aada-mgr		
ABURA-ASEBU-KWAMANKESI DISTRICT ASSEMBLY CASE WORKER 1	aakda-cw-1		
ABURA-ASEBU-KWAMANKESI DISTRICT ASSEMBLY CASE WORKER 2	aakda-cw-2		

Note that local administrators and supervisors will likely only see Users in their own User Groups or Agency.

- Users whose roles have the “Access all records or users in my group” level of access will see all Users in their User Groups.
- Users whose roles have the “View (Within Agency)” permission on Users will see only Users within their own Agency.

Creating Users

To create a new User account, click the **New** button at the top of the Users List page.

The screenshot shows the 'USERS' configuration page. The sidebar on the left lists various settings, with 'USERS' being the active section. The 'Users' setting is expanded, revealing a form with the following fields:

- Full Name ***: A text input field.
- Username ***: A text input field.
- User Code**: A text input field.
- How should Primero set the user's password? ***: A dropdown menu.
- Locale**: A dropdown menu.
- Role ***: A dropdown menu.
- User Groups ***: A dropdown menu.

At the top right of the form, there are two buttons: 'CANCEL' and 'SAVE'.

For each user, you must specify the following information:

- **Full Name** - This is the actual name of the User.
- **Username** - Users will enter this every time they login. For this reason, it is recommended to keep the username short.
 - Each User's username should be unique.
 - In addition, the username will be visible on any records created by the User. For this reason, implementation partners should discuss a consistent username pattern. This can include an Agency abbreviation, some indication of the User's day-to-day work (e.g. including 'cw' for case workers), and/or some part of the User's actual name. As partners discuss a pattern, they should attempt to balance the need for Users to be able to understand which person they are dealing with when they read a username; with the need to avoid revealing too much personally identifiable information about the User.
 - Note that if your implementation uses Identity Providers to handle User accounts, the username will need to match a specific format. For more information, please see the [Managing Identity Providers](#) section of this guide.
- **User Code** - This attribute is not used in most implementations. Unless your configuration is using the User Code to generate composite record IDs, you can ignore this.
- **How should Primero set the User's password?** - Here, you have two options:
 - "I will set the password" - If you select this option, you will be asked to enter the password, then confirm it (to guard against typos). You will then be responsible for communicating this password to the User.
 - "User will set the password using the welcome email" - If you select this option, you do not need to set the password. A password reset email will be sent to the User, and they will be able to set their own password.
- **Locale** - The language in which the User will see Primero.

- **Role** - Must be an existing role as defined in the section above. This controls both the User's permissions and level of record access. For more information, please read the [Roles](#) section of this guide.
- **Modules** - A user is given access to one or more modules in Primero. For example, a Child Protection Officer will likely only have access to the CP (or "Child Protection") module. And a GBV Case Worker will likely only have access to the GBV (or "Gender-Based Violence") module.
- **User Groups** - Must be an existing user group or groups as defined in the section above. For managers, this will determine which records they can access. For more information on how User Groups influence which records a User sees, please read the **User Groups** section of this guide.
- **Agency** - The organization to which the user belongs.
- **Location** - The location where the user is based. Please note that this will be used for
 - *Reporting*: All records created by the User will be listed as being created in this Location
 - *Referrals*: When a User is creating a Service for their Case or performing a Referral, they can filter Users by Location to find a User who is close to them.
- **Services** - The services which the user is capable of providing. Note that this will be used to determine whether this User appears as a potential recipient when other Users are planning Services and Referrals. If you leave this field blank, the User will automatically be given the Services their Agency is configured to provide.
- **Phone** - While this does not currently affect any Primero functionality, it can help administrators and supervisors contact the User.
- **Email** - Welcome, password reset, and notification emails will be sent to this email address. Note that emails are enabled on both demo and production environments.
- **Position** - This does not affect any Primero functionality. The "Position" of the user is meant to capture the User's precise job title, which may not be properly explained by the Role the User has been given.

Note: Since a User's **Location**, and **Services** settings are used to determine whether a User appears as a potential recipient for a Service or a Referral, it is important that administrators regularly update users' accounts to reflect any changes to the Services they provide or their Location. For more information on the Referral workflow, please see the [Agency Services](#) section of this guide.

Note: If no email exists, then the administrator will select "I will set the password" in the user profile and in the email that can be entered in the user profile is "their username"@instance URL" so it would look like: jpanchalingam@newyork.primero.org

Editing Users

To edit an existing user, click on the User in the Users List. Then, on the Show User page, click the **Edit** button. Editing a User account is mostly the same as creating one, with the exception that you cannot update a User's username once their account has been saved.

Once you are done making changes, please remember to click **Save**.


Limitations on editing your own account

Please note that, while users may sometimes be able to edit their own user accounts, no user may edit which role, user groups, modules, or agency are assigned to their user account. Primero uses this precaution to ensure users do not grant themselves additional power and endanger the data confidentiality of clients.


Updating Passwords

There are two ways to update a User's password.


- **Edit the account:** When you edit a User's account, click the **Change Password** link. A modal will appear. Enter the User's new password, then confirm it. Click the **Update** button at the bottom of the Change Password modal, then click **Save** on the Edit User page.

The image shows a 'Change Password' modal form. It has two input fields: 'Password' and 'Password Confirmation', both with masked text (dots). Below the fields is a red rectangular button labeled 'Change Password'. The modal itself is titled 'CHANGE PASSWORD' and has a close button (X) in the top right corner. At the bottom of the modal are two buttons: a blue 'UPDATE' button with a checkmark icon and a grey 'CANCEL' button with an X icon.


- **Send password reset email:** Go to the User list, and click on the User whose password you would like to reset. At the top of the screen, in the **Actions** menu, click the **Send password reset email**. The user will receive an email containing a link which they can use to reset their password.



In addition, Users can always reset their password by clicking the **Forgot your password?** link at the bottom of the Login page.



The User will see a modal where they can enter the email address associated with their User account. They will then receive an email containing a link they can use to reset their password.




Note: Because Primero often uses password reset emails to help Users set their password, it is *extremely important* that administrators specify an email address for User accounts whenever possible.

Managing Identity Providers

Some implementations in Primero v2 will use identity providers to manage User accounts (i.e. Users can login using their organizational credentials, such as a UNICEF or IRC username / email address). In implementations configured to use identity providers, creating and updating user accounts will work slightly differently.

- When creating a user account, you must first specify a provider.



- Based on the provider you have selected, you will need to enter a username which matches that provider's username format. For instance, in this example, I have accepted "IRC" as the User's identity provider. Therefore, I must enter a username that ends in "@rescue.org".

Identity Provider *

IRC

Full Name *

Sherlock Holmes

Username *

shelock.holmes@rescue.org

Example: my.username@rescue.org

- Once you create this User account, the user will receive a welcome email like the one below, telling them how to login.

Welcome to [integration-id.primerodev.org!](https://integration-id.primerodev.org/)

You have been added as a CP Case Worker.

1. Go to <https://integration-id.primerodev.org/> and click IRC.
2. Login with your IRC account shelock.holmes@rescue.org.
3. Use the same password you always use for your IRC account.

Please contact Jack Miszencin (miszenci@quoininc.com) for further details.

- **Note:** Primero administrators do not manage passwords for users who login with an identity provider account. All password management is performed by the identity provider.

Organizations Without Identity Providers

In some systems which have been configured to use identity providers, there will still be some organizations who do not use an identity provider. To create User accounts for these organizations, use the “Primero” identity provider.

Identity Provider *

UNICEF

Quoin

Primero

Jozian

IRC

Once you have selected the “Primero” provider, you will enter a username which ends in the Primero site’s URL.

Identity Provider *
Primerio
Full Name *
John Watson
Username *
john.watson@integration-id.primerodev.org
Example: my.username@integration-id.primerodev.org


When you create this User account, the User will receive a welcome email containing a temporary password. **Note:** At this point, you as the administrator will be responsible for sending the user their Primerio username so that they can login.

Welcome to integration-id.primerodev.org!

You have been added as a CP Case Worker.


1. Please contact Jack Miszencin (miszenci@quoininc.com) to receive your user name.
2. Go to <https://integration-id.primerodev.org/> and click "login with Primerio user name."
3. Login with your user name and the temporary password 2n3rloqKmTEWHn8SRudACnYvz.
4. When prompted, reset your password.

If the User clicks on the link in the email, they arrive at the Login page, where they click **Login with Primerio username**.




The screenshot shows a login interface with a blue header and a white content area. The title 'LOG IN' is at the top. Below it, the text 'Select provider' is followed by four blue buttons: 'UNICEF', 'Quoin', 'Jozian', and 'IRC'. At the bottom of the provider list, there is a link 'Or log in with Primerio username' which is highlighted with a red rectangular box. To the right of the provider list is a large, light gray rectangular area.


At this point, a separate window will open where the User will be prompted to enter their Primerio username, then their temporary password.



Note that, once the User resets their password and signs in, they will be prompted to set up and verify a recovery email address and phone number. This is important, to ensure that Users have a way of recovering their account should they lose access.




The User may also be asked if they would like to “stay signed in.” For security reasons, it is not recommended that Users do so.



From this point forward, all password management and resets will be handled through the Primero identity provider interface accessed through the Login page. **In order to update the password for users using the Primero Identity, please go to <https://aka.ms/sspr>.**

Disabling Users

Please note that Users cannot be deleted. Instead, administrators can “disable” a User account by editing the User, then checking the “**Disabled**” tick box. Disabling a username will prevent that username from being used to log in to Primero.



Other Settings

Managing Tasks for CPIMS+

The below table outlines which fields set each Case Workflow Task in the Task List:

Task	How to set this status (Trigger field)	Trigger field ID
<i>Assessment Due</i>	Fill out the Assessment Due Date field.	assessment_due_date
<i>Assessment Completed</i>	Fill out the Assessment Start Date field.	assessment_requested_on

<i>Case Plan Due Date</i>	Fill out the Case Plan Due Date field.	case_plan_due_date
<i>Case Plan Completed</i>	Fill out the Case Plan Start Date field.	date_case_plan
<i>Service Due</i>	Fill out the Service Due Date field.	service_appointment_date
<i>Service Completed</i>	All services are implemented (Service Implemented field has value "implemented"). User sets a service as implemented by filling out the Service Implemented On field.	service_implemented_day_time
<i>Follow up Due</i>	Fill out the Follow Up Needed By field.	followup_needed_by_date
<i>Follow up Completed</i>	Fill out the Follow Up Date field.	followup_date

Managing Workflow Statuses for CPIMS+

The below table outlines which fields set each Case Workflow Status:

Workflow Status	How to set this status (Trigger field)	Trigger field ID	Developer settings	NOTES
<i>New</i>	[Set by default on case creation]			
<i>Assessment</i>	Fill out the Assessment Start Date field.	assessment_requested_on	Only appears as a workflow status if the module has the " use_workflow_assessment " attribute set to true. This attribute defaults to false, so if you do not set this attribute, this workflow status will not appear by default.	
<i>Case Plan</i>	Fill out the Case Plan Initiated field.	date_case_plan	Only appears as a workflow status if the module has the " use_workflow_case_plan " attribute set to true. This attribute defaults to false, so if you do not set this attribute, this workflow status will not appear by default.	

<i>Response Type 1, Response Type 2, etc.</i>	Service created with a Response Type value of Response Type 1, Response Type 2, etc.	service_response_type	Options are set in the Service Response Type lookup. If all service provisions fall under the same step in your workflow, we suggest changing the Service Response Type lookup to have a single option, labelled "Service Implementation", and set this to be the default value for the "service_response_type" field.	Each of these is intended to represent a different category of service provision, which represents a different stage of case management.
<i>Services Implemented</i>	All services are implemented (Service Implemented field has value "implemented"). User sets a service as implemented by filling out the Service Implemented On field.	service_implemented_day_time	Only appears as a workflow status if the module has the " use_workflow_service_implemented " attribute set to true. This attribute defaults to true, so if you do not set this attribute, the status will show automatically.	
<i>Closed</i>	Set Case Status to "Closed"	child_status		
<i>Reopened</i>	Perform Reopen action	case_status_reopened		

Managing GBVIMS+ KPIs

KPIs will display the "owned_by_location" admin level set in the reporting_location_config. In the example below, the admin level displaying in the KPIs are the case worker who owns the case's location AND the location in their user profile must be set to admin 2 or admin 3 or higher. If this requires to be changed, a developer must change it via the system settings.

```

▼ reporting_location_config: {field_key: "owned_by_location", admin_level: 2,...}
  admin_level: 2
  ▼ admin_level_map: {0: ["country"], 1: ["province"], 2: ["district"]}
    ► 0: ["country"]
    ► 1: ["province"]
    ► 2: ["district"]
  field_key: "owned_by_location"

```

Managing Configurations

As you make configuration changes, you can save your settings in a **Configuration**. This acts as a snapshot of all your configuration settings at a point in time. Later, when you have made other configuration changes, if you want to undo them, you can find your saved **Configuration** and apply it to return your system to how things were configured at that point in time.


What do configurations include?

- Roles
- User Groups
- Agencies
- Forms
- Lookups
- Reports

What do configurations NOT include?

- Cases
- Incidents
- Tracing Requests
- Locations
- Contact Information
- Users
- Note: User Groups can also be added directly into production

To view all your saved Configurations, click the **Settings** link in the navigation menu, then click the **Configurations** link in the Settings navigation menu. You will arrive at the Configurations List page.



The screenshot shows the Primero application interface. On the left is a navigation sidebar with links for Online, Home, Cases, Incidents, Tracing Request, Reports, Exports, Support, primero, and Settings. The main content area is titled 'CONFIGURATIONS' and features a '+ NEW' button. Below the title is a table with columns: NAME, VERSION, DESCRIPTION, DATE CREATED, and LAST APPLIED ON. The table contains three rows of configuration data. At the bottom of the table, it indicates 'Rows per page: 20' and '1-3 of 3'.

NAME	VERSION	DESCRIPTION	DATE CREATED	LAST APPLIED ON
A baseline config from demo-pawtucket	20210122.183203.423f1b6	test	22-Jan-2021 19:32	
Testing Promotions #2	20210121.005328.fdb9f09	This is it	21-Jan-2021 01:53	
Testing Promotion	20210120.015831.bedb395		20-Jan-2021 02:58	

Creating Configurations

To create a new Configuration, click the **New** button at the top of the page.

NEW CONFIGURATION ✓ SAVE

Clicking Save will create a record of all current configuration settings (example: Roles, Agencies, Forms) at this point in time. After you save, you can push these changes to another instance of Primero. If, in the future, you make configuration changes which you wish to undo, you can apply this Configuration record to restore all of the configuration changes you had at this point in time.

Name *

Added the Age Assessment form

Description

Added the Age Assessment form, then gave the Case Worker Role access to this form.

Enter a Name and Description, then click **Save**.

Applying Configurations

To apply a Configuration you had previously created, click into the Configuration in the Configurations list. You will see information on the Configuration, including when it was created, who created it, and when it was last applied.

Primerio

✓ Online

Home

Cases

Incidents

Tracing Request

Reports

Exports

Support

primero

Settings

SETTINGS

A BASELINE CONFIG FROM DEMO-PAWTUCKET

DELETE

✓ APPLY

⚙ SEND

Users

Roles

User Groups

Agencies

Forms

Locations

Contact Information

Configurations

Audit Logs

Name *

A baseline config from demo-pawtucket

Description

test


Version

20210122.183203.423f1b6

Date Created

22-Jan-2021 00:00

Click the **Apply** button at the top of the page. The site will be unavailable momentarily to *all* users while the Configuration is applying. For this reason, it is important to only apply Configurations during periods of low site usage.



Once your Configuration has applied, Users should experience the system configuration as it existed when the Configuration was first created.

Note: You will not be able to apply a Configuration which was created on a higher version of Primero than the one you are using. For instance, if you create a Configuration on your sandbox site, which is running Primero v2.1.1, then send that Configuration to your production site, which is running Primero v2.1.0, you will not be able to apply the Configuration on production until the production site is also upgraded to v2.1.1.


Note: Applying a past Configuration will not delete configuration records such as Agencies and User Groups which were created after that Configuration was saved. Instead, these will be *disabled*, which will limit their visibility in the system. For instance, suppose you save a Configuration titled “Added Agency A” on March 1, then create Agency B on March 2. If, on March 3, you apply the “Added Agency A” Configuration, Agency B will still exist in your system, but will be disabled. This will mean that any Users assigned to Agency B on March 2 will still exist and function normally, but administrators will no longer be able to assign new Users to Agency B.

Sending Configurations to Production


As mentioned in the [Where to Make Configuration Changes](#) section, it is recommended that you make configuration changes on a sandbox or “demo” site, test them, then send them to your production site to be applied. This translates into the below steps:

- Make configuration changes on your sandbox site.
- Save a Configuration with your changes on the sandbox site.
- Test your changes on the sandbox site.
- Once you have tested your changes, *send* your Configuration to the production site.
- At a time of low production site usage, *apply* your Configuration on the production site.
 - **Note:** You should always communicate your plans to apply a Configuration on the production site with implementation partners.

To send a configuration from your sandbox site to your production site, go to the Configurations list on your sandbox site. Click into the Configuration you want to send. Click the **Send** button at the top of the page.



You will see a confirmation message warning you that the Configuration will need to be manually applied on the production site. Click **Send** again.



Login to your production site and go to the Configurations list. Find the Configuration you just sent from the sandbox site and click it. Click the **Apply** button to apply the Configuration to your production site.

Limits on Configuration management in Production

Note that, since you will be making most of your configuration changes on the sandbox or “demo” site, you will not be able to make some configuration changes on the production site except by applying a saved Configuration. This means you will not be able to create or update the following resources on the production site:

- Forms
 - Note that this includes updates to fields and translations.
- Lookups
- Agencies
- Roles

You will still be able to make changes to the following resources on production:


- Reports
- User groups

- Users
- Contact Information
- Locations

Note: the configuration changes made to production directly do not need to be saved in production. The reports, user groups, users, contact information and locations will remain in production.

Code of Conduct

When initially logging onto Primero, users will be prompted to review and accept a code of conduct:



The code of conduct is editable through the "Settings" under "Code of Configuration". Administrators can modify the terms of the code of conduct as defined by the programme.



Online

Home

Cases

Incidents

Tracing Request

Reports

Exports

Support

primero

Settings

Log out

SETTINGS

CODE OF CONDUCT

Users

Roles

User Groups

Agencies

Forms

Locations

Contact Information

Code of Conduct

Configurations

Audit Logs

Title *

CODE OF CONDUCT – FOR ALL PRIMERO USERS

Content *

This Code of Conduct applies to Primero users. All user organisations must sign a Terms of Use and adhere to its provisions. Individual Primero users must personally commit to the following Code of Conduct. All will work in the best interest of the children and survivors of violence.

1. I am responsible for the data that I gather in Primero. I will conduct my work according to the principles of Informed Consent, Need to Know, Do No Harm and the Best interests of the Child.

Created on

09-Apr-2021 16:08

Created by

primero

EDIT

Error Messages in Primero

In order to support you when you receive a specific error message on your browser when you are using Primero, please follow the below guidance:

Are you seeing this error message?	What does it mean?	What do you do?
A popup indicating you need to either log back in or press continue.	The session has been inactive and this pop up appears after 5 minutes of idle time.	You can either log back in or press continue to resume with the session.
error: [missing "en.forms.record_type s.undefined" translation]	There is a translation that is missing when you are trying to make a request.	Send a screenshot to the Primero System Administrators skype chat and describe the process of what you were trying to do so the team can debug the issue.
errors.api.internal_server	This is a generic error given when the server cannot process something you are requesting.	Wait a few minutes and try again. If the error continues, watch this video and send a message to the Primero System Administrators skype chat or the Primero Support Hub informing the team. Please include your country/URL, what day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.
Unexpected token "<," '<html> <h' ... is not valid JSON	This is an issue in the JSON code and needs to be fixed by the developers.	Watch this video and send a screenshot of the error to the Primero System Administrators skype chat or the Primero Support Hub informing the team. Please include your country/URL, what day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.

errors.api.internal_server failed to fetch	This is a network error given when the server cannot process something you are requesting.	Do you see your logo in the bottom left corner of the navigation? If not, please reload your screen. If you still see the error, please log out and log in again. Were you attaching a file? If yes, are your attachments successfully attached? If not, log out and log back in again. If the error continues, watch this video and send a message to the Primero System Administrators skype chat or the Primero Support Hub informing the team. Please include your country/URL, what day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.
400 Bad Request	The server cannot process the request due to an error from the user or the user's device.	Try the following options in the order below: 1. Double check the website address. 2. Refresh. 3. Log out and log back in. 2. If that does not work, clear your browser's cache or cookies. 3. Send a message to the Primero System Administrators skype chat to help debug.
403 Forbidden	You do not have access to a specific functionality within Primero.	Reach out to the Primero team on the functionality you were trying to access and they will be able to provide you with further guidance. Please provide us with the role that got the forbidden error, the website/URL and please describe what you were trying to do (for example, trying to save a case, add a user, etc.).


500 Internal Server Error	This is a generic error given when the server cannot process something you are requesting.	Send a screenshot to the Primero System Administrators skype chat. Please include your country/URL, what day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.
502 Bad Gateway – Microsoft Azure Application Gateway	The server is not available and the infrastructure team needs to get the system back up.	Wait a few minutes and try again. If the error continues, send a message to the Primero System Administrators skype chat or the Primero Support Hub informing the team. Please include your country/URL, what day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.
504 Gateway Timeout	This error indicates an issue with your network connection or server communication speed.	Wait a few minutes and try again. Refresh your screen. If the error continues, send a message to the Primero System Administrators skype chat or the Primero Support Hub informing the team of the day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.
This site can't be reached	This error indicates an issue with your network connection or server communication speed.	Try the following options in the order below: 1. Check connectivity 2. Refresh your page. 3. If that does not work, try "Incognito mode". 4. If that does not work, try a different browser. 5. If that does not work, try with different devices.

		6. Send a message to the Primero System Administrators skype chat to help debug.
ActiveStorage::FileNotFoundError	This error indicates there is an error with one of the photos added within one or many of the agencies.	1. Go to each agency and verify if there is a photo added under the large / icon logo 2. If there is no logo present, go to the next agency 3. If a logo appears, verify that both files are PNG files 4. If one of the files is not PNG, please re-upload the logo and refresh your screen and save the configuration to resolve the error.
Syncing data: not able to see data that has been saved (including attachments)	The user saves a case or uploads a document and presses save. The data isn't appearing when logged in as a supervisor, or the user is not able to see their downloads.	1. Check the change log to see if the updates were saved to the case 2. If the data is in the change log, check if you are in "online" mode 3. If you are in "online" mode, inform the Primero team of the user name and time when the error occurred. 4. The Primero team may also ask you to take a screenshot of "Network" and "Error" tabs in your Inspect console to help troubleshoot.

Connection refused - {data=>"fq=type=type %AChild&fq=....	The volume of storage has run out.	1. Send the Primero team a message with a screenshot of the error. 2. The Primero team will increase the size of the disk volume storage for SOLR (submit a PR for this if vendor)
JSON.parse: unexpected character at line 1 column 1 of the JSON data		Watch this video and send a screenshot of the error to the Primero System Administrators skype chat or the Primero Support Hub informing the team. Please include your country/URL, what day and time when you saw this error and describe the process of what you were trying to do so the team can debug the issue.

Failed to replace fields because one or more of the new records could not be saved		
--	--	--

You can also debug by opening up the “Network” section of the Inspect console to see where errors may occur. Sharing a screenshot such as the one below is the most useful in a debugging process.



GBVIMS+ KPIs/Pulse

The KPIs/Pulse is a feature of GBVIMS+ which is a set of performance-monitoring indicators and dashboards tailored for GBV programming. This will only work for GBVIMS+ users.

In order to ensure the KPIs work correctly, please follow the below steps:

- 1) All case workers and supervisors should have the lowest admin level set on their user profile. This is their “reporting location” which appears in the GBVIMS+ home page, filters, and KPIs/Pulse. Please see additional guidance on locations [here](#).

Settings **Users Aymal khan**

Phone

Email *

aymaikhan.salarzai@rescue.org

Agency *

IRC

Position

Location *

ZANZIBAR UNGUJA MJINI MAGHARIB MAGHARIB B FUONI KIBONDENI

☐ Disabled

☒ Receive email notifications?

☒ Approval Request (Managers)

☒ Approval Response (Case Workers)

☒ Assignments, Transfers, and Referrals

☒ Transfer Requests

☐ Receive push notifications?

Note that you will still need to allow push notifications on your device's browser.

- 2) The type of location should also include “County” as admin 1 or 2. Please see additional guidance on the type of locations for GBVIMS+ [here](#).

☐	NAME	CODE	ADMIN LEVEL	TYPE	HIERARCHY
☐	Somalia	SO	0	Country	SO
☐	Somalia:Awdal	SO11	1	County	SO, SO11
☐	Somalia:Awdal:Borama	SO1101	2	District	SO, SO11, SO1101

- 3) Check the Role of the users who need to view the Pulse/KPIs and ensure they have the permissions to view them:

Settings **Role GBV Case Management Supervisor**

☐ View

Pulse/KPIs

- ☒ Access Pulse/KPIs Page.
- ☒ Assessment Status
- ☒ Average Followup Meetings per Case
- ☐ Average Referrals
- ☐ Case Closure Count
- ☐ Caseload
- ☐ Client Satisfaction Rate
- ☐ Completed Case Action Plans
- ☐ Completed Case Safety Plans
- ☐ Completed Action Plan Approved by Supervisor
- ☐ Number of Cases
- ☐ Number of Incidents
- ☐ Reporting Delay
- ☐ Services Provided
- ☐ Supervisor to Caseworker Ratio
- ☐ Time from Case Open to Case Closed

- 4) Verify that none of the fields used in the table below are hidden or modified in the configuration:

KPI Number	Fields Used	Form Used	Help Text
------------	-------------	-----------	-----------

1. Number of recorded Cases	System Fields		This indicator measures how many newly reported cases are opened each month per site for the past 3 months. A reporting site is understood as the site where the User Organization is providing services and where the case was reported to the service provider.
2. Number of recorded Incidents	System Fields		This indicator counts the number of new reported incidents opened each month per site for the past 3 months. A reporting site is understood as the site where the User Organization is providing services and where the incident was reported to the service provider.
3. Reporting Delay	date_of_first_report and incident_date	Incident Details	This indicator provides information related to the number of days that have lapsed between when the survivor experienced GBV and when the survivor first reported it to a service provider. It is calculated based on when the incident was first reported. The data is presented based on different length of time (0-3 days; 4-5 days; 6-14 days; 15-30 days; Over 1 month; Over 3 months). This indicator can be filtered for cases under a certain period of time (past month, 3 months; 6 months; 1 year).
4. Assessment Status	assessment_family_situation (Survivor's family situation (for adults)) assessment_current_living_situation (Survivor's current living situation) assessment_presenting_problem (Reasons for seeking case management services) assessment_current_situation (Current situation	Survivor Assessment Form	This indicator calculates the proportion of active cases for which an assessment form was completed. An assessment is considered completed where a set of mandatory fields within the 'Survivor assessment' form group under the CASE tab of Primero/GBVIMS+ platform.

	and imminent risks)		
5. Completed Case Safety Plans	safety_plan_needed safety_plan_developed _with_survivor safety_plan_completion _date safety_plan_main_concern safety_plan_preparedness_signal safety_plan_preparedness_gathered_things	Safety Plan Form	This indicator calculates the proportion of active cases for which a safety plan was deemed necessary and completed (ex. intimate partner violence, suicide/homicide risk, child protection). A safety plan is considered completed where a set of mandatory fields within the 'Safety plan' form group under the CASE tab of Primero/GBVIMS+ platform.
6. Completed Case Action Plans	service_type service_referral service_referral_written _consent	Action Plan→Action Plan Subform	This indicator calculates the proportion of active cases for which a Case Action Plan was completed. A case action plan is considered completed where a set of mandatory fields within the 'Action plan' form group under the CASE tab of Primero/GBVIMS+ platform.
7. Case Action Plans Approved by Supervisor	action_plan_approved (plus all from KPI 6)	Action Plan	This indicator calculates the proportion of active cases for which a Case Action Plan was completed AND reviewed/approved by a supervisor. A case action plan is considered completed where a set of mandatory fields within the 'Action plan' form group under the CASE tab of Primero/GBVIMS+ platform.
8. Services Provided	service_type_provided	Action Plan → GBV Follow Up	This indicator identifies the type of services provided to survivors at entry point or start of case management process. By service provided, we mean the service that is provided by the User organization in-house, not service provided by referrals to other services.
9. Average Referrals	service_referral	Action Plan → Action Plan Subform	This indicator counts the average number of referrals done for each recorded case (for all type of services)

Referrals per service			This indicator calculates the number of referrals made per type of service (ex. safe house/shelter, health/medical, psychosocial, legal assistance, safety and security and livelihood services) per month
10. Average Follow-Up Meetings per Case	follow_up_date	Action Plan → GBV Follow Up	This indicator counts the average number of follow-up meetings conducted for every active case over a set period of time per case worker on the platform.
Average Follow Up Meetings per Case			This indicator counts the average number of follow-up meetings conducted for every active case over a set period of time.
11. Progress Made towards Goals	gbv_assessment_progress_safety gbv_assessment_progress_health gbv_assessment_progress_psychosocial gbv_assessment_progress_justice gbv_assessment_other_goals	Action Plan → GBV Follow Up	This indicator measures the percentage of cases for which goals have been met by type of needs (e.g. safe house/shelter, health/medical, psychosocial, legal assistance, safety and security and livelihood services). This indicator is informed by the section 'Progress made towards goals' under the 'Follow up' section of the 'Action plan' form group in the CASE tab.
12. Time From Case Open To Case Close	date_closure	GBV Case Closure	This indicator Measuring how long cases are kept open, how long the case management process takes from the initial report to User Organization to case closure. The length of time is broken down by the following timeframe: less than 1 month; between 1 and 3 months; between 3-6 months; more than 6 months.
13. Case Closure Rate	date_closure	GBV Case Closure	This indicator measures how many cases closed per month per site. A reporting site is understood as the site where the User Organization is providing

			services and where the incident was reported to the service provider.
14. Client Satisfaction Rate	opening_hours_when_client_could_attend client_comfortable_with_case_worker same_case_worker_each_visit could_client_choose_support_person client_informed_of_options client_decided_what_next client_referred_elsewhere survivor_discreet_access staff_respect_confidentiality client_private_meeting staff_friendly staff_open_minded staff_answered_all_questions staff_client_could_understand staff_allowed_enough_time staff_helpful client_feel_better would_client_recommend_friend	Client Feedback Form	This indicator measures the ratio (percentage) of survivors who completed the Feedback Survey who are satisfied with the case management services provided to them.
15. Supervisor To Caseworker Ratio	System Fields		This indicator is monitoring the number of caseworkers a supervisor supervises in order to intervene if needed. This calculation is based on the system roles allocated on the platform (Benchmark of 1:5 and no larger than 1:8)
16. Case Load	System Load		This indicator measures the average caseload per caseworker based on open cases. The ration of cases to case workers is divided based


			on the following breakdown: less than 10 open cases, between 10-20 open cases, between 21-30 open cases, more than 30 open cases (Benchmark 1:15 active cases, at the most 1:20)
--	--	--	--


Primero Reporting using Power BI and the Cases API

Purpose: This is a step-by-step guide for pulling case data from Primero Cases API into Power BI for data visualization.

- 1) **Make sure you understand what an API is and how it works.** An API is a way for two digital systems to securely communicate and share data. In Primero, the API works like any other user, based on the permission of that user's role. It allows raw data to be shared digitally without having to extract it (via export) from Primero. APIs can do different things, but for our purposes we are going to use the "GET" data and "POST" data requests. Read more [here](#).
- 2) **Check to make sure you have access to cases in your Primero instance.** Only users with existing access to case records will have permissions on the Cases API. Any user can access the API endpoint for something they would normally access in the UI. If you can see the case list in the Primero UI, you can also access the Cases API. If you can access users in the Primero UI, you can also make requests to the Users API. For the purposes of doing powerbi analysis on cases, a user would need to have view access to cases (edit access not necessary). To limit the access a user has to specific information about cases in the API, you would update which case forms their role has access to.
- 3) **Always consider data privacy and data protection first.** Access to case data should always be confidential. If you intend to access the Cases API, this access should be approved by the relevant authorities and be in-line with your information sharing protocols and regulations. If you are creating a new role for reporting using the API, make sure that this role is designed, tested and approved by the relevant authorities. *DATA PROTECTION IS YOUR RESPONSIBILITY.*
- 4) **Do a little research on Power BI.** What is it? What can it do? What type of needs do you have? What type of account do you have? Learn about visualizations, dashboards, reports, apps, and datasets (Power BI content) and workspaces. You can find lots of relevant information and videos online. Start [here](#)


- 5) **Think about the data you want to use in Power BI.** It's important to think ahead about what you want to do. You need to have a **clear purpose** for your use of the data. What relationship(s) do you want to show? Think this through before you set up your API call.
- 6) **Make sure you understand how the API parameters work.** To make sure you are getting the right information from the API, it is important to understand how to use an API endpoint's URL parameters. Take the time to learn about these before getting started.
- Here is a quick guide on how to format URL parameters:
<https://apipheny.io/what-are-api-parameters/>
 - Here is the documentation for the Cases API:
<https://github.com/primerolMS/primerol/blob/master/doc/api/cases/get.md>
 - Note that the Incidents and Tracing Requests API endpoints will have approximately the same guidelines as those laid out in the documentation for the Cases API. The endpoints for these are:
 - Incidents: `/api/v2/incidents`
 - Tracing Requests: `/api/v2/tracing_requests`
- 7) **Prepare to make your API call.** Every time you have PowerBI pull information from the Cases endpoint, you will need to enter a URL. When asked to pick an authentication, choose "Basic auth," and enter your username and password.
- a) If your implementation uses single sign-on, you will need to use a different authentication method.
- i) First, in your browser, go to Primero and sign in.
- ii) Next, open your browser's developer tools. In Chrome, you right-click anywhere on the page and click "Inspect." Then click into the "Network" tab.





(2)

- iii) Now, in Primero, click on the Cases list.
- iv) In the “Dev tools” window, in the Network tab, click on the most recent request in the list.



(1)

- v) When you do this, details of the request will appear on the right. In this pane, scroll down until you reach the section labeled “Request Headers.” Find the header called “authorization.” Highlight the whole value of this header, including the word “Bearer.” Copy this.

- vii) When you click “OK,” you will be automatically authorized. Note that this authorization header value which you copied will expire roughly once every 30 minutes. If you have trouble connecting to the API after a certain point, try repeating the steps here.

When entering a URL, you may want to add the following parameters:

- **fields:** This tells the API which fields to include in its response. By default, the API will only send back all available fields on the case. Passing in the **fields** parameter limits the size of the JSON response and only includes the information you need to analyze. This last part is very important for preventing the leaking of sensitive data. Remember that any data you have on your laptop is a potential security risk. Not including the **fields** parameter can cause the response to time out, cause PowerBI to crash if the response size is too large, and can lead to you having sensitive information on your laptop.
 - Example: to only include the Protection Concerns and Risk Level fields, you would add the following parameter to your URL:
`fields=risk_level,protection_concerns`
- **per** and **page:** The first of these two parameters tells the API how many Cases to include in the response, while the second tells the API which page of results you would like to review. Just like when you are viewing the Case list in Primero, if you leave these blank, the API will default to showing 20 results per page and showing you the first page of results. To view a large number of results, you can either set the **per** parameter to a very large number (e.g. 10000) or do multiple requests to the API, increasing the **page** parameter every time.
 - Examples:
 - To include 500 results per response, and view the second page of results, add the parameters `per=500&page=2`.
- **General filtering parameters:** You can add in parameters that filter the results based on field values. Note that this gets formatted differently for different types of fields.
 - Example: To only include Cases between the ages of 10 and 15, and with the protection concerns “Unaccompanied” or “Separated, add the parameters `sex=male&age=10..15&protection_concerns=unaccompanied,separated`

- 8) **Submit your API call.** PowerBI can pull the JSON response from this API and import it for analysis.

Primero and RapidPro

In order to get RapidPro to create cases within Primero, or to edit fields within existing cases in Primero, we need to use the Primero API. RapidPro's Call *Webhook* node type allows us to interact with APIs such as the Primero API in a RapidPro flow.

You only need to do these steps once per integration of RapidPro and Primero.

Accessing the Primero API requires credentials. Generally, it is best practice to create a RapidPro specific user which can only access a minimal set of resources. Once the user has been created, you should take note of its username and password.

As we will be using these credentials over a long period of time, it is most straightforward to use *Basic Auth* to authenticate to our webhook.

In order to generate a *Basic Auth* string, you need to encode the credentials into Base64. If you are using a MacOS or Linux machine, you can do this in a shell with the following command:

```
printf '<username>:<password>' | base64
```

Alternatively, you can use a tool such as [Postman](#) or [Httpie](#) to try out various API commands (and generate a basic auth string).

Once you have determined what your *Basic Auth* string is, you can save it to a global variable in the relevant RapidPro workspace. It is possible to access the global variables at **/global**

on your rapidpro instance. You should also set the URL of your primero instance to a global variable.

NOTE: All users with permissions on Rapidpro workspace can access this global variable. They can therefore access any resource that the rapidpro user can access on Primero. Only give RapidPro access to trusted users.

Creating cases

The most common thing we are likely to do with rapidpro is to create a case. In order to do that, we first need to create a "Call Webhook" node. There are three tabs with configuration details that need to be set.

The first tab is the one that opens by default. In this tab, you need to set the HTTP verb to *POST*, and set the URL of the webhook. You will be able to do this by referencing the global variable you created earlier (@globals.primer_url in the screenshot below). After the global variable, you need to set the route, which for cases will be **/api/v2/cases/**. If you wanted to create an incident, it would be **/api/v2/incidents/**

Call Webhook

HTTP Headers ✓POST Body ✓

When a contact arrives at this point in your flow...

Call a webhook

POST

@globals.primerio_url/api/v2/cases/

If your server responds with JSON, each property will be added to the Flow.

```
{ "product": "Solar Charging Kit", "stock level": 32 }
```

This response would add `@webhook.product` and `@webhook["stock level"]` for use in the flow.

Result Name

initial_webhook

By naming the result, you can reference it later using `@results.initial_webhook`

CancelOk

Click on the second tab HTTP headers. Primerio expects the following headers:

- 1) accept
- 2) authorization
- 3) content-type

You may find the *accept* and *content-type* headers automatically set. If they are not set, set them to the values in the below screenshot. You will also need to set the *authorization* header. This will reference the global variable you created earlier for the *HTTP Basic Auth* string (in the screenshot, it is called `@globals.primerio_auth_string`

Call Webhook

HTTP Headers ✓POST Body ✓

Add any additional headers below that you would like to send along with your request.

Accept	application/json
Authorization	@globals.primerio_auth_string
Content-Type	application/json
Header Name	Value

Cancel

Ok

In the **post body** tab, we set the data we will send to Primero. It will usually be populated with some pre-existing content when a new webhook node is created, but we will need to set it ourselves.

RapidPro uses its own expression language to evaluate templates in flows. The documentation for the expression language can be found [here](#).

Primerio expects JSON to be sent to its API endpoints. This JSON is usually easier to template literally rather than using the JSON function in rapidpro (but care will need to be exercised so as to avoid any risk of quoting errors or injection).

Call Webhook

HTTP Headers ✓POST Body ✓

POST Body

Modify the body of the POST request that will be sent to your webhook.

```
module_id: "primarymodule_id",
"legitimate_basis": [
  "legal_obligation"
],
"identification_date": "@(today())",
"entry_point_source_of_the_complaint_11b0034": "sms_chatbot_cee40c8",
"is_this_a_sea_case_8fcda5a": "true",
"type_of_complainant_fa3e386": "@results.complainantcategory.category"
}
```

Modify the body of the POST request that will be sent to your webhook.

Cancel

Ok

If you are updating a case this is largely similar to creating cases, but instead of a POST request, we will send a PATCH request. The payload is a lot simpler as well.

In the first tab, here the main difference to creating a case is that we specify the case ID in the URL. If the case ID is stored from earlier in a result, you can use that in the url.

Call Webhook

HTTP Headers ✓PATCH Body ✓

When a contact arrives at this point in your flow...

Call a webhook

PATCH

@globals.primerio_url/api/v2/cases/@results.case_id

If your server responds with JSON, each property will be added to the Flow.

```
{ "product": "Solar Charging Kit", "stock level": 32 }
```

This response would add `@webhook.product` and `@webhook["stock level"]` for use in the flow.

Result Name

Result

By naming the result, you can reference it later using `@results.result`

Cancel

Ok

In the second tab (http headers), this is the same as for creating a new case.

When PATCHING a case, we only need to provide the fields we want to update. For example, if you have stored a result in rapidpro at *results.consent* and you want to save the category of that result (like yes or no) to Primero, you can do the following. *consent.reporting* is the database name on Primero's side that you want to save your result to.

Call Webhook

HTTP Headers ✓ PATCH Body

PATCH Body

Modify the body of the PATCH request that will be sent to your webhook.

"data": @Uson(object('consenLreporting', results_consent_category:t)))}

Modify the body of the PATCH request that will be sent to your webhook

Cancel

If you would like data to go from Primero to RapidPro, there are features released in 2.12 to allow this to happen. Specific requirements are required to ensure this request is properly set up by developers.

Primero System Settings Configuration for Software Teams and Developers Only

Primero is an information management system that allows for data entry and reporting for child protection. The system helps intake relevant information via multiple sources, consolidates the information into relevant record types (Cases / Incidents / Tracing Requests) and allows service providers to report and make educated decisions to assist in these locations.

In version 1 of Primero, there were many features that needed to be updated by a developer. In v2, many of these features are enabled through the front-end UI for system administrators to be able to manage their programme. This includes:

- User management functionality (ability to create and edit users, user groups, agencies and roles which include the ability to manage sending email notifications, creating an incident from, adding a service to a case/incident you do not own, ability to see the view page or "short form" to preview a case, a case or receiving approvals for assessments, case plans or case closures)

- Customizable forms and lookups functionality (ability to create and edit forms and lookups including the ability to reorder form groups, delete subforms or make a field required)
- Locations management (ability to upload locations that will appear in dropdown lists)
- Updating the Code of Conduct, Terms of Use and Support pages

Though many configuration choices can be made directly by a system administrator or a Primero Technical Team member, there are configuration choices that can be requested for a new deployment of Primero which must be made by a developer.

Languages


When deploying a new instance of updating an instance of Primero, system administrators, or focal points responsible for setting up the instance, can request languages to suit the programme/context. Application strings must be translated through Transifex. Forms can be translated through Transifex or through the Forms editor. Languages have corresponding locale codes for example:

- 'en': English
- 'fr': Français
- 'ar': Arabic
- 'ar-LB': Lebanese Arabic
- 'so': Somali
- 'es': Spanish
- 'bd': Bangla
- 'id': Bahasa / Indonesian
- 'ku': Kurdish

This is key to note, as these locales will be referenced and used when importing locations.

Reporting Location Configuration

The "Reporting location config" in the System Settings sets the location levels used for the Dashboard and Filters. Note the "role" permission which has a reporting location for the role technically overrides it. As a developer, you can include multiple admin levels in 1 label. For example, you can include "'1' => [governorate, camp]" and then both governorates and camps will be included. Note that these options need to be included in the **location type lookup** and typed exactly as they appear in the location type lookup.



```
reporting_location_config: {
  field_key: 'owned_by_location',
  admin_level: 2,
  admin_level_map: { '1' => ['province'], '2' => ['district'] }
},
```

If you would like the dashboard to not display registered cases by district, the dashboard can be updated by a developer to display cases by the current location of the child (db: current_location). To do this, update the field_key to 'current_location'.

Search by ID

Search by ID modal is a pop-up that allows users to search by an ID before creating a case. This can be turned on and off in the Modules:

```
module_options: {
  allow_searchable_ids: true,
},
```

Search Bar

The fields which are used in the search bar are configurable. For instructions on which fields are searchable and how to modify those fields go to the instruction here:

<https://community.primero.org/t/how-can-i-see-what-fields-are-searchable-how-do-i-refine-my-searches-so-i-only-pull-back-relevant-data/526>

Composite Case ID

Composite Case ID can be updated to a specific format requested by the programme which ends in a 7-figure Case ID GUID (case_id_display). For example, the programme may request

“Registration Date” and “Case ID” which would look like “12/24/2022/u8347di”. For instructions on how to update this in v2, follow steps in this instruction:

<https://community.primerio.org/t/modifying-the-composite-id-in-primerio-v2/531>

CASE ID can be also customized to include location and agency following the below instruction:

```
"field_key"  "case_id_code"
"format"
    "created_by_user.Location.ancestor_by_type(district).location_code"
    "created_by_user.Location.ancestor_by_type(chiefdom).location_code"
    "created_by_user.agency.agency_code"

"separator"  "-"
"auto_populated"  true
```

Note: this is not possible to do for incident ID or other IDs in Primerio at this time

IDs in Primerio

The Long ID (case_id) is a 26 character long series of characters generated by an algorithm and virtually guaranteed to be unique. This makes for a convenient means of finding a very specific record. Since this series of characters is so long and hard to remember, though, there is also a Short ID (short_id), which is simply the last seven characters of the Long ID. Both Long ID and Short ID are automatically included in all exports as a means of distinguishing between records. Another identifier that is important is the Case ID (case_id_display) which is a series of characters determined by a pre-set formula which, while still keeping the individual behind the case anonymous, should be more recognizable to a worker. For instance, the Case ID could be the abbreviation for the district where the record was registered plus a dash, the last letter of the child's first name, the day of the month when the child was born, and the Short ID. Such a pattern gives no vital information about the individual, but allows the case worker to distinguish easily between records. The Case ID is displayed on the case list view and is searchable in the search bar. Lastly, Record ID (id) is the key ID of the case which is on the database and is the same series of letters and numbers seen in the in URL. This is another unique identifier for a case.

Age Range

The age ranges can be updated through the system settings by a developer by updating these fields:

```
age_ranges: {
  primerio: [0..2, 3..4, 5..9, 10..12, 13..14, 15..17, 18..999],
  unhcr: [0..4, 5..11, 12..17, 18..59, 60..999]
```

```
}
```

Alerts

You can update the label for the alerts for Assessment, Case Plan and Closure for each language in Primero. For example for English you can change the approval labels here:

```
approvals_labels_en: {  
  assessment: "BIA",  
  case_plan: "Case Plan",  
  closure: "Closure",  
  action_plan: "Action Plan",  
  gbv_closure: "GBV Closure"  
},
```

You can also set which forms have the alerts appear, for example, you can change alerts to appear on “Basic Identity”:

```
approval_forms_to_alert: {  
  assessment_status: 'assessment',  
  cp_case_plan: 'case_plan',  
  closure_form: 'closure'  
},
```

You can also turn off all alerts:

```
show_alerts: true,
```

Emails

There are notification emails which can be turned on or off for any functionality regardless of the “User” receiving emails:

```
notification_email_enabled: true
```

Welcome email is set at the deployment and can be turned off in the user profile:

```
welcome_email_enabled: true,
```

The content of the Welcome Email can be configured in the “welcome_email_text:” and is pre-configured in the baseline.

Data Protection and Privacy/Legitimate Basis

“data_protection_case_create_field_names” should be an empty array if you would like to turn this feature off.

Full Name Field

By default the CPIMS+ includes an auto-generation of Full Name where users fill in the First, Middle, and Last Name fields and the Full Name is auto-populated from those fields. The Full Name field is not editable. The property to add to the field in the config is `hidden_text_field` with a value of true or false. And this can also be turned off in the Forms section as an administrator.

Services Tasks

Another attribute in the System Settings portion of the configuration bundle which cannot be edited through the administrator interface is that which controls how services become due. The 'due_date_from_appointment_date' attribute, set to be false by default, can be manually set to true in order to make each service become due based on the the "Appointment Date" field (or any field on the services subform with the id "service_appointment_date"). When this attribute is instead set to false, a service instead comes due based on the "Implementation Timeframe" field (or any other field on the services subform with the id "service_response_timeframe").

Updating List Filters and List Headers

A module can now specify which column headers and filters it has appearing in the record list view. Please note that the headers / filters you specify must be one of the hard-coded available headers or filters specified in the `models/header.rb` and `models/filter.rb` files. See example below:

```
list_filters: {  
  cases: %w[  
    approval_status_case_plan risk_level last_updated_at flagged  
    owned_by my_cases workflow owned_by_agency_id status displacement_status  
    approval_status_assessment  
    approval_status_closure protection_risks location_current reporting_location  
    cases_by_date record_state  
  ]  
},  
list_headers: {  
  cases: %w[
```

```

        case_id_display short_id complete client_code owned_by location_current
flag_count alert_count

    ]

},

```

You can also override the labels for some app strings within the system settings. The list of strings available for override is limited but is continually being updated. You can find the current available list in the file *app/javascript/components/application/use-system-strings.js*. Below is an example.

```

field_labels_en: {
  'dashboard.protection_concerns' => 'Client Issues',
  protection_concerns: 'Client Issues'
}

```

API

In order to set up the API role properly you will follow these steps:

- 1) The development team will set up an API form. This form will be composed of fields that should be shared for interoperability.
- 2) The development team will set up a role for interoperability. The role itself will need to be provided both read and edit access to the forms needed for interoperability such as the API form, and the the Services form (if you are doing service referrals).
- 3) The development team will set up a user for interoperability using the above role.

If a time sync is needed OpenFn can set this, and the webhook can be triggered every time an update is made on a case.

All API documentation can be found here:

<https://github.com/primerolMS/primerol/blob/master/doc/api.md>

Editing the Workflow Status Bar

A combination of lookups and attributes in the System Settings can be used to control the various workflow statuses that a case can have. Please note that any changes to the workflow statuses should only be made after significant testing on VMs and discussion with the local steering committee.

Three workflow statuses are always enabled, and will display in the workflow bar no matter what values exist in the lookups. These are "New," "Reopened," and "Closed." It is important to note that only one of the first two of these will display at a given time, with "New" appearing in the bar

by default, and "Reopened" only appearing if the case has been reopened after being closed. In this scenario, the "New" status will not appear at all.

Some statuses (associated with the service currently being implemented) come from the "Service Response Type" lookup. The default values for this lookup are "Care plan," "Action plan," and "Service provision." However, any entries made here will appear in the workflow status bar. If a user adds a non-implemented service to an open case and gives it a response type, the case's workflow status will be set to this new service's response type. For example, if I have an open case, and I have added a service that has not yet been implemented and has a response type of "Action plan," the workflow status for the case will then be "Action plan." If multiple non-implemented services have been added, the case's workflow status will be the response type of the most recently-added service. Note: Since the settings in the following section can only be set manually in the user bundle, this section is only for developers working on the user bundle.

There are three more potential workflow values: "Assessment," "Case Plan," and "Service Implemented." Although none of these are set to appear in the workflow status bar by default, each can be enabled for a given module using the `use_workflow_assessment`, `use_workflow_case_plan`, and `use_workflow_service_implemented` attributes, respectively, for whichever module where you want to use the status. Set any one of these attributes to true to use the corresponding workflow status. For instance, to enable the "Assessment" workflow status in the default configuration bundle, search for "PrimerModule." You should come to a list of all the modules in the system. By default, there should be only one, with an id of "primeromodule-cp." Within the object representing this module, set the `use_workflow_assessment` attribute to true. You may end up with something looking like the lines pictured below. If you then re-import the bundle with this change, you should see the "Assessment" workflow status show up in the workflow status bar.

For example, case plan and service implemented are turned on if:

```
use_workflow_service_implemented: true,  
  use_workflow_case_plan: true,  
  use_workflow_assessment: false,
```

To update the labels for any of the status bar, go to Lookups and click on the Workflow look up (`workflow_lookup`). Update accordingly.

Hiding the Workflow Status Bar

If the workflow status bar is required to be hidden then it can be updated through the system settings:

```
module_options.workflow_status_indicator
```

Enabling Field Mode

```
system_settings = SystemSettings.current
system_settings.system_options['field_mode'] = true
system_settings.save!
```

Adding Other Reportable Fields

Within the reports you are able to generate reports based on the locations listed below:



We also are able to generate a report by:

- Created-by user
- Owned-by user
- Created-by user groups
- Owned-by user groups

In order to enable these fields, here are the ids of the fields found in the standard interagency "Other Reportable Fields" form:

- Created_by
- Owned_by
- Created_by_groups
- Owned_by_groups

Note that some of these may actually already be found in an implementation's other reportable fields form, and if so, you should just make sure they're formatted the same way as in the interagency forms.

Adding IDP

Documentation:

https://unicef.visualstudio.com/ICTD-PRIMEROX-IM/_wiki/wikis/ICTD-PRIMEROX-IM.wiki/2584/Primero-Manual-Changes-for-Developers

Transitioning from non-IDP to IDP

Below are the steps to transition from non-IDP to IDP:

1. ICTD/Quoin to switch to SSO with IDPs
2. Create new users
3. Match old/new users
4. Reassign old/new users
5. Disable old users

Remove Password Encryption from Exports

In the Helm release, developers can disable password encryption by updating the PRIMERO_ZIP_FORMAT;"none"

```

18 values:
19   application:
20     primero:
21       primeroStorageType: "microsoft"
22       primeroStorageazContainer: "activestorage"
23       keyvaultName: "pmx-prd-primero-kv"
24       POSTGRES_HOSTNAME: "pmx-prd-primero-psql-11.postgres.database.azure.com"
25       acrLoginServer: "uniprimeroxacrdev.azurecr.io"
26       runConfigscripts: true
27       configurationRepo: "unicef.visualstudio.com/ICTD%20-%20Primero%20X%20DEV/_c
28       configurationRepoGitRevision: "UNRWA.20220801.01"
29       relativeConfigurationPath: "/primero-x-configuration/implementations/cpims-
30       branchToPromoteProductionFrom: "master"
31       implementation: "unrwa-cm-sand"
32       tlsCertKVName: "tls-primero" Automated Account, 3 months ago • pipelin
33       LOCALE_ALL: "en,ar"
34       PRIMERO_DEFAULT_USERS: "false"
35       PRIMERO_SANDBOX_UI: "true"
36       PRIMERO_PROMOTE_CONFIG_PROD_HOST: "unrwa-cm.primero.org"
37       PRIMERO_CODE_OF_CONDUCT: "true"
38       PRIMERO_DATA_PROTECTION_CASE_CREATION: "false"
39       PRIMERO_ONBOARDING_ADMIN_EMAIL: "ajit.shetty@trigyn.com"
40       PRIMERO_ONBOARDING_ADMIN_FULL_NAME: "Ajit Shetty"
41       PRIMERO_ONBOARDING_ADMIN_AGENCY_NAME: "UNICEF"
42       PRIMERO_ONBOARDING_ADMIN_AGENCY_CODE: "UNICEF"
43       PRIMERO_ZIP_FORMAT: "none"
44     image:
45       tag: "v2.4.3"
46   global:

```

Turning on alerts and email notifications for updates on a case by a non-record owner

Field in SystemSettings that takes a list of the fields to send the email alerts on. The form has to be added to the list in settings.

A caseworker is assigned to a case where they have some shared responsibility with another agency. There is a different worker that is part of a different agency that gets referred onto the case. That different worker will update certain fields on the case which will trigger an alert (and email) to be sent to the original case worker. If the original case worker then subsequently changes those fields, the other agency case worker will get alerted.

Duplicate Record Alerts

You can enable Duplicate Record Alerts - and set the field(s) Primero will use when searching - by adding something like the below into the system settings.

```
'duplicate_field_to_form' => {
  'case' => {
    'national_id_no': 'basic_identity',
    'unhcr_individual_no': 'referral_details'
  }
}
```

These settings translate as follows:

- If someone creates a case with a "national_id_no" value which has already been used for this field on another case, the new case will get a "Duplicate Record" alert on the "basic_identity" form.
- If someone creates a case with a "unhcr_individual_no" value which has already been used for this field on another case, the new case will get a "Duplicate Record" alert on the "referral_details" form.


Overdue Cases to Assign Dashboard


The “Overdue Cases to Assign” dashboard can be customized by a specific due date in the system settings:

```
"timeframe_hours_to_assign
timeframe_hours_to_assign_high" These two variables set the timeframes for the Need
Assignment dashboard. A high-risk case is considered "overdue" if it was registered before
timeframe_hours_to_assign_high hours ago, while all others are considered overdue if they
were registered before timeframe_hours_to_assign hours ago. "timeframe_hours_to_assign:
3
timeframe_hours_to_assign_high: 1"
```

Customize the theme and logos in Primero



Follow this instruction to change the branding, palette and styling features of the Primero app, including login page (colors/gradient, logo backdrop “pictorial”, logo), dashboard and list view. Requirements and formats for graphics and logos are included. Configuration settings are included. Below are images of what exactly can be configured (see labels / arrows):





Requirement for logos:

- 2 transparent png logos with white space trimmed on the outside. One logo should be legible for darker background and the other for lighter backgrounds. It's recommended that the current logo for lighter backgrounds and changing the text in the logo to white for darker backgrounds. It's also recommended to keep the width to less than 600px
- A pictorial (just the icon) that is a transparent png also with the outside trimmed in the following sizes
 - 144px by 144px
 - 192px by 192px
 - 256px by 256px
- A transparent .ico file that will be used for the favicon with the size of 48px by 48px
- Optional we can upload a background images behind the login area. That should be a transparent png with the minimum size of 400 x 300. It's recommended that the pictorial is in a solid white color



PROTECTION CONCERN	ALL CASES	OPEN CASES	NEW (THIS WEEK)	CLOSED (THIS WEEK)
Separated	6	6	0	0
denial_of_resources_opportunities_or_services	6	6	0	0
child_labour	14	13	0	0
child_survivor_of_explosive	7	6	0	0
rape	6	6	0	0
lack_of_documentation_birth_registration	9	7	0	0
Orphan	13	10	0	0
Difficulty communicating	7	7	0	0
functional_difficulty_hearing	6	5	0	0
child_marriage	12	11	0	0
functional_difficulty_remembering	6	4	0	0
In conflict with the law	10	9	0	0
slavery_sale_abduction	11	10	0	0
difficulty_with_self_care	14	13	0	0
sexual_exploitation	16	12	0	0
Other	12	9	0	0
functional_difficulty_walking	9	8	0	0
Unaccompanied	11	10	0	0
Serious medical condition	13	11	0	0

Enabling Registry, Family Records and new forms for existing instances

When enabling new functionalities such as the registry or family records which do not exist within instances, there are a series of configuration updates that need to be made:

1. Create a Primero Configuration backup
2. Add Form Groups lookup (for families and registry)
3. Add forms and fields (ie. any fields that currently exist in the family details' form, should be added to the family member subform)
4. Create a new Primero Configuration, promote it and apply it
5. Associate the module with the form added. Note that this needs to be done manually in demo and production (only in production once the lookups and forms are promoted)
6. Update role, assign permissions actions and permit forms

Additional Primero Servers for Config Promotion

In Primero X, a demo instance is configured to promote the Primero configuration to a single production instance. Optionally, additional Primero servers can be set up to receive the configuration.

The additional servers will need to have configuration promotion user and role configured. To do so, obtain the secret value of PRIMERO_PROMOTE_CONFIG_PROD_BASIC_AUTH that is on the demo server. Then:

- Copy the file primero-x-configuration/common/users/service_accounts.rb to the Primero/Rails home directory on the target machine.

- Run
PRIMERO_PROMOTE_CONFIG_PROD_BASIC_AUTH=<secret-value> rails r
service_accounts.rb

On the demo server add the new target Primero instance. Log on to the demo instance and open up the Rails console. In the console run the following commands, replacing <new-server-host>:

```
system_setting = SystemSettings.first
system_setting.primerio_promote_config = [{
  "tls" => "true",
  "host" => "<new-server-host>",
  "port" => "443",
  "basic_auth_secret" => "PRIMERO_PROMOTE_CONFIG_PROD_BASIC_AUTH"
}]
system_setting.save!
```

Restart the demo instance (the application and worker container server to reload system settings).

On the new server:

Create a configuration promotion user with the username and password identified from \$PRIMERO_PROMOTE_CONFIG_PROD_BASIC_AUTH. If this server uses third party identity authentication, make sure that the user object has the field `service\_account` set to true. Assign the Role "Configuration promotion - DO NOT EDIT!". If the Role does not exist, it must first be created with this script:

```
...
Role.create_or_update!(
  unique_id: 'role-config-promotion',
  name: 'Configuration promotion - DO NOT EDIT!',
  permissions: [Permission.new(resource: Permission::CONFIGURATION, actions:
[Permission::MANAGE])],
  referral: false,
  modules: PrimeroModule.all
)
```

When a system administrator clicks the **Send** button on a configuration, the configuration will be sent to both the original production server and the new server.

Note that `system\_setting.primerio\_promote\_config` is an array of hashes. Additional target machines may be configured.

GBVIMS+ Incident Recorder

The GBVIMS+ has a specific export called the Incident Recorder, or IR. This is used in a specific consolidation process for global reporting on the GBVIMS+. Below are the fields that populate the GBVIMS+ Incident Recorder:

ID	DISPLAY NAME	SUBFORM
incidentid_ir	INCIDENT ID	
survivor_code	SURVIVOR CODE	
date_of_first_report	DATE OF INTERVIEW	
incident_date	DATE OF INCIDENT	
date_of_birth	DATE OF BIRTH	
sex	SEX	
ethnicity	ETHNICITY	
country_of_origin	COUNTRY OF ORIGIN	
marital_status	CIVIL / MARITAL STATUS	
displacement_status	DISPLACEMENT STATUS AT REPORT	
disability_type	PERSON WITH DISABILITY?	
unaccompanied_separated_statuses	UNACCOMPANIED OR SEPARATED CHILD?	
displacement_incident	STAGE OF DISPLACEMENT AT INCIDENT	
incident_timeofday	INCIDENT TIME OF DAY	
incident_location_type	INCIDENT LOCATION	
incident_location	INCIDENT COUNTY	
incident_location	INCIDENT DISTRICT	

incident_camp_town	INCIDENT CAMP / TOWN	
gbv_sexual_violence_type	GBV TYPE	
harmful_traditional_practice	HARMFUL TRADITIONAL PRACTICE	
goods_money_exchanged	MONEY, GOODS, BENEFITS AND / OR SERVICES EXCHANGED ?	
abduction_status_time_of_incident	TYPE OF ABDUCTION	
gbv_reported_elsewhere	PREVIOUSLY REPORTED THIS INCIDENT?	
gbv_previous_incidents	PREVIOUS GBV INCIDENTS?	
(counts #of subforms)	No. ALLEGED PRIMARY PERPETRATOR(S)	
perpetrator_sex	ALLEGED PERPETRATOR SEX	perpetrator
former_perpetrator	PREVIOUS INCIDENT WITH THIS PERPETRATOR	perpetrator
age_type	ALLEGED PERPETRATOR AGE TYPE	perpetrator
age_group	ALLEGED PERPETRATOR AGE GROUP	perpetrator
perpetrator_relationship	ALLEGED PERPETRATOR - SURVIVOR RELATIONSHIP	perpetrator
perpetrator_occupation	ALLEGED PERPETRATOR OCCUPATION	perpetrator
service_referred_from	REFERRED TO YOU FROM?	service
service_safehouse_referral	SAFE HOUSE / SHELTER	service
service_medical_referral	HEALTH / MEDICAL SERVICES	service
service_psycho_referral	PSYCHOSOCIAL SERVICES	service
pursue_legal_action	WANTS LEGAL ACTION?	service

service_legal_referral	LEGAL ASSISTANCE SERVICES	service
service_police_referral	POLICE / OTHER SECURITY ACTOR	service
service_livelihoods_referral	LIVELIHOODS PROGRAM	service
service_protection_referral	CHILD PROTECTION SERVICES / EDUCATION SERVICES	service
consent_reporting	CONSENT GIVEN	
created_organization	REPORTING AGENCY CODE	

Frequently Asked Questions

What are the limits of attachments per case?

This is adjustable but out of the box each instance set up can accommodate 100 attachments max. at 20MB per attachment.

Single sign on is not working for me. What can I do to ensure it is working for the user?

First check the user profile and make sure the email and user name are the same email address. If they are the same, then reach out to the Primero team focal point. They will ask you to verify the JWT token. To do this in the browser go to Inspect. Have the user try and sign in. Go to the network tab, then the tokens section and copy the authorization. Paste this without the bearer into jwt.io (this is a legitimate website).

How do I set up Primero to test out Referrals?

When testing out Primero's referral functionality, you may decide to set up some test agencies, roles, and users, so that you can fully play out the referral workflow: planning a service, referring the case, logging in as the referral recipient and accepting the referral, then finally recording service details and marking the service as done.

Here are the configuration items you will want to put in place before performing the referral workflow:

- Roles:
 - You will need two roles: one for the user sending the referral, and another for the user receiving it.
 - Sending the referral (typically the case worker role):
 - The role of the user sending the referral should have the **Case > Refer Case from Service** subform permission

- This role should also have edit access to the **Services** form.
 - Receiving the referral (typically the service provider role):
 - The role of the user receiving the referral should have the **Case > Receive Referral** permission. Also make sure this user has access to adequate forms on the case, including the Services form.
- Agencies:
 - Make sure the agency of the user receiving the referral is listed as providing whatever service you want to refer the case for. For instance, if you want to refer for a **Medical Service**, make sure one of your agencies has this service listed.
- Forms:
 - In the Services subform, make sure the following fields are visible:
 - Type of Service
 - Implementing Agency
 - Service delivery location
 - Service provider name
 - Service implemented (select dropdown)
 - Service completed (date-time field)
 - Notes on the referral from provider (NOTE: This field is filled out automatically with any notes the service provider records when they mark the referral as “Done.”)
- Users
 - You will need two users: one to send the referral, and another to receive it.
 - Sending the referral
 - Make sure this user gets the role you set up for sending the referral (see above).
 - Also note that it is best to practice sending a referral on a case which this user owns, since only the case’s record owner (or their manager) can see all the referrals in the Referrals form.
 - Receiving the referral
 - Make sure this user gets the role you set up for receiving the referral (see above).
 - Make sure this user belongs to the Agency you set up for providing the service. On a related note, when you create this user, leave the **Services** field blank, and make sure that after creation, the user gets all the same services as their agency. This ensures that when you select a service for referral (e.g. Medical Services), both the example agency and this user will appear as options in the Services subform.
 - Give this user a location which is at the standard “reporting location” level for your implementation. Typically, this is the third administrative level or “District” level. Remember the location for this user, since you will be using it later.

Example

- Login to the test site as a CP Administrator

- Set the CP Case Worker role to have edit access to the Services form and the “Refer from Services subform” permission on Cases.
- Set the CP Service Provider role to have edit access to the Services form and the “Receive Referral” permission on Cases.
- Go into the services subform and make sure that all referral-relevant fields (see list above) are visible. They should also all be enabled, except for “Notes on the referral from provider”
- Create a new “Hospital 1” agency, with the ability to perform the Medical service type.
- Create a new user with the CP Service Provider role. Give them the username “hospital-1-sp” Make them part of the new Hospital 1 agency, and leave the Services field blank, so that they inherit the Medical service type from their agency. Set their location as “Iraq:Duhok:Duhok”
- Login to the test site as the CP Case Worker test user.
 - Go to any case for which you are the record owner. Edit.
 - Make sure are consent fields are set to “Yes.”
 - Add a service subform.
 - For “Type of Service, select “Medical”
 - For “Implementing Agency,” select “Hospital 1”
 - For “Service delivery location,” set “Iraq:Duhok:Duhok.”
 - For “Service provider name,” set “hospital-1-sp”
 - Finish adding the service subform, then save the case.
 - In the Services subform, click the Refer button on the service you just added.
 - In the Refer modal, leave a note for the service provider, then click Refer.
- Login to the test site as hospital-1-sp
 - In the dashboard, click on the number for “Total Referrals.” Make sure you see the case which the case worker just referred to you. Click this.
 - Go into the Referrals subform and click the actions button (“...”) on the Referral which has been sent to you. Click Accept, then click through the confirmation modal. Note that you are now responsible for this referral’s service.
 - Edit the case. You can now manually add some information to the service. Save.
 - Now, in the Referrals subform, click the actions button (“...”) on the Referral which has been sent to you. Click Done. In the confirmation modal, leave some information in the notes field. Then click Done to confirm you have finished with the referral.
- Log back in to the test site as the case worker
 - Click the “New & Updated” number in the dashboard. Note that you arrive at a case list which includes the case you had referred previously. Click into it.
 - In the Referrals form, note that it is listed as Done, and that a note has been left there about the service, from the service provider.
 - In the Services subform, note that there is an alert at the top of the form, telling you that someone updated the form.

- Note that the Service Implemented field has been updated to say the service is implemented, and that the Service Completed date field is set to the current date.
- Note that the “Notes on the referral from provider” field is filled in with the note that the service provider left in the Referral “Done” confirmation modal.
- Note that the workflow status has been updated to Service Implemented. NOTE: This workflow status does not appear in all implementations.